



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**SGI**  
**SGI 2400 32X 400MHz R12k**

SPECint\_rate2000 = **125**  
SPECint\_rate\_base2000 = **115**

SPEC license #: 4 | Tested by: SGI | Test date: May-2000 | Hardware Avail: Jun-2000 | Software Avail: Apr-2000

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	32	633	82.1	32	610	85.2
175.vpr	32	375	139	32	361	144
176.gcc	32	356	115	32	355	115
181.mcf	32	387	173	32	341	196
186.crafty	32	302	123	32	305	122
197.parser	32	643	104	32	607	110
252.eon	32	362	133	32	365	132
253.perlbnk	32	741	90.2	32	737	90.7
254.gap	32	569	71.8	32	576	70.9
255.vortex	32	657	107	32	360	196
256.bzip2	32	457	122	32	410	136
300.twolf	32	673	166	32	672	166

### Hardware

CPU: R12000  
 CPU MHz: 400  
 FPU: Integrated  
 CPU(s) enabled: 32 cores, 32 chips, 1 core/chip  
 CPU(s) orderable: 2-64  
 Parallel: No  
 Primary Cache: 32KBI + 32KBD on chip  
 Secondary Cache: 8MB(I+D) off chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 32GB  
 Disk Subsystem: 1 x 18 GB SCSI, 10 x 18 GB FC (striped)  
 Other Hardware: None

### Software

Operating System: IRIX 6.5.8f  
 Compiler: MIPSpro 7.3.1.1m C, C++, Fortran90  
 File System: xfs  
 System State: Single-user

## Notes/Tuning Information

Baseline optimization flags (C and C++ use same flags):

PASS1 : -Ofast=ip27 -IPA:use\_intrinsic -fb\_create /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

PASS2 : -Ofast=ip27 -IPA:use\_intrinsic -fb\_opt /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

Portability Flags:

176.gcc: -DUSG -Dalloca=\_\_builtin\_alloca -DMIPS -DHOST\_WORDS\_BIG\_ENDIAN

186.crafty: -DSGI

253.perlbnk: -DSPEC\_CPU2000\_SGI -DI\_FCNTL

254.gap: -DSYS\_IS\_USG -DSYS\_HAS\_TIME\_PROTO -DSYS\_HAS\_SIGNAL\_PROTO -DSYS\_HAS\_IOCTL\_PROTO

300.twolf: -DHAVE\_SIGNED\_CHAR

Peak optimization flags:

note: all occurrences of (FEEDBACK) below means compiled with a two-step process:

PASS1 = -fb\_create /tmp/SPEC2000/FBDIR\_peak/\$(EXEBASE)

PASS2 = -fb\_opt /tmp/SPEC2000/FBDIR\_peak/\$(EXEBASE)

164.gzip: -Ofast=ip27 -IPA:space=500:plimit=500 -lmalloc (FEEDBACK)

175.vpr: -Ofast=ip27 -IPA:space=300:plimit=10000: callee\_limit=5000:linear=on -LNO:prefetch Ahead=2

. -INLINE:aggressive=on -OPT:Olimit=0:alias=disjoint:alias=restrict -lmalloc (FEEDBACK)

181.mcf: -Ofast=ip27 -IPA:min\_hot=14 -lmalloc (FEEDBACK)

176.gcc: -Ofast=ip27 (FEEDBACK)

186.crafty: -Ofast=ip27 -LNO:prefetch=0 -OPT:goto=off -lmalloc (FEEDBACK)

197.parser: -Ofast=ip27 -IPA:min\_hot=14 (FEEDBACK)

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**SGI**  
**SGI 2400 32X 400MHz R12k**

**SPECint\_rate2000 = 125**  
**SPECint\_rate\_base2000 = 115**

SPEC license #: 4 | Tested by: SGI | Test date: May-2000 | Hardware Avail: Jun-2000 | Software Avail: Apr-2000

## Notes/Tuning Information (Continued)

```

252.eon: -Ofast=ip27 -LNO:prefetch=0 -LANG:exceptions=off -lmalloc (FEEDBACK)
253.perlbnk: -Ofast=ip27 -IPA:use_intrinsic -Wl,-x (FEEDBACK)
254.gap: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4
. -OPT:alias=restrict:alias=disjoint -IPA:min_hot=7 -lmalloc (FEEDBACK)
255.vortex: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4 -LNO:opt=0
. -CG:ld_latency=5 -IPA:min_hot=14 -TENV:X=4 -IPA:space=500:plimit=3600 -OPT:goto=off (FEEDBACK)
256.bzip2: -Ofast=ip27 -IPA:min_hot=5:space=500:plimit=2900 -INLINE:aggressive=on (FEEDBACK)
300.twolf: -Ofast=ip27 -IPA:use_intrinsic (FEEDBACK)

```

The following O/S parameters were set:

```

setenv PAGESIZE_DATA 4096
setenv PAGESIZE_TEXT 4096
setenv PAGESIZE_STACK 4096
systune -i ; percent_totalmem_4m_pages = 50 ; nlpages_4m = 128
limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```

rm -rf /tmp/SPEC2000 ; mkdir /tmp/SPEC2000 ; cd /tmp/SPEC2000 ; mkdir FBDIR_base ; mkdir FBDIR_peak

```