



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMEPOWER800/1000/2000 (788MHz)

SPECint_rate2000 = 105
SPECint_rate_base2000 = 90.1

SPEC license #: 22 | Tested by: Fujitsu Limited | Test date: Aug-2002 | Hardware Avail: Sep-2002 | Software Avail: May-2002

250	200	150	100	50	Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
					164.zip	16	318	81.7	16	280	92.7
					175.vpr	16	326	79.6	16	289	89.9
					176.gcc	16	311	65.7	16	222	91.9
					181.mcf	16	368	90.8	16	337	99.1
					186.crafty	16	201	92.2	16	154	120
					197.parser	16	349	95.8	16	315	106
					252.eon	16	232	104	16	191	126
					253.perlbnk	16	324	103	16	281	119
					254.gap	16	412	49.6	16	404	50.6
					255.vortex	16	247	143	16	188	188
					256.bzip2	16	285	97.8	16	271	103
					300.twolf	16	493	113	16	449	124

Hardware

CPU: SPARC64 GP
 CPU MHz: 788
 FPU: Integrated
 CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
 CPU(s) orderable: 4 to 16/4 to 32/8 to 128
 Parallel: None
 Primary Cache: 128KBI+128KBD on chip
 Secondary Cache: 8MB(I+D) off chip, per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 16GB
 Disk Subsystem: 1 x 36GB, 1 x 18GB SCSI (10000rpm)
 Other Hardware: Ethernet

Software

Operating System: Solaris 8 2/02 with patches 108434-07 and 108435-07.
 Compiler: Fujitsu Parallelnavi 1.0.2
 with patches 911403-01 and 911746-01.
 Sun ONE Studio 7 with current patches (see notes)
 Sun Performance Library 7
 File System: ufs
 System State: multi user

Notes/Tuning Information

Baseline (except 252.eon, for Parallelnavi 1.0.2): -Kfast_GP=3,largepage

fdo_pre0=rm -rf `pwd`/*.fbk

PASS1=-Kpg

PASS2=-Kpu=\$(EXEBASE).fbk

(252.eon, for Sun ONE Studio 7): -fast -xcrossfile

fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache

PASS1=-xprofile=collect:`pwd`/../feedback

PASS2=-xprofile=use:`pwd`/../feedback

Peak

(for Sun ONE Studio 7)

fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache

PASS1=-xprofile=collect:`pwd`/../feedback

PASS2=-xprofile=use:`pwd`/../feedback

164.zip: -x05 -xtarget=ultra3 -xalias_level=std -W2,-whole -xcrossfile
-W2,-Ainline -xprefetch -Wc,-Qgsched-trace_late=1,-Qgsched-spec_load=1 -l12amm

175.vpr: -fast -xarch=v8plusb -xalias_level=std -xcrossfile -xsfpcnst
-xdepend -W2,-whole,-Mt600,-Mr4000 -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1,-Qeps:rp_filtering_margin=100
-xregs=syst -xprefetch=auto,latx:5.0 -lprism32 -lmopt -lm

176.gcc: -fast -xtarget=ultra3 -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -l12amm



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMEPOWER800/1000/2000 (788MHz)

SPECint_rate2000 = 105
SPECint_rate_base2000 = 90.1

SPEC license #: 22 | Tested by: Fujitsu Limited | Test date: Aug-2002 | Hardware Avail: Sep-2002 | Software Avail: May-2002

Notes/Tuning Information (Continued)

```

186.crafty: -fast -xtarget=ultra3 -xarch=v8plus -xF -xinline= -xcrossfile -Wc,-Qgsched-spec_load=1,-Qiselect-funcalign=64
           -xalias_level=strong -xregs=syst -W2,-Ashort_ldst,-Aivel:duplicate_loops -xprefetch=auto,latx:5.0
197.parser: -fast -xarch=v8plusb -xdepend -xprefetch=no%auto
           -xcrossfile -xregs=syst -Wc,-Qgsched-trace_late=1,-Qgsched-T4
           -xalias_level=strong -Wc,-Qipa:valueprediction
           -W2,-Ashort_ldst,-Mt5000 -Wc,-Qiselect-funcalign=32 -lprism32
252.eon: -fast -xtarget=ultra3 -xcrossfile -xalias_level=compatible -xsafe=mem -Qoption iropt
          -Mt2000,-xrestrict -Qoption cg -Qgsched-trace_spec_load=1,-Qgsched-trace_late=1
253.perlbnk: -xO5 -xtarget=ultra3 -xarch=v8plusb -xcrossfile -xalias_level=strong -xsafe=mem
            -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qgsched-trace_spec_load=1 -Wc,-Qinline_memcpy=32
            -Wc,-Qiselect-funcalign=32,-Qicache-chbab=1 -Wc,-Qiselect-sw_pf_tbl_th=20 -W2,-Adata_access -xprefetch=auto,latx:5.0 -l12amm -dn
255.vortex: -fast -xtarget=ultra3 -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Ms1,-Mt600,-Mr13000,-crit
            -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32 -Wc,-Qpeep-Sh0
            -xrestrict -xdepend -W2,-Amemopt
            -l12amm -lprism32
256.bzip2: -fast -xtarget=ultra3 -W2,-whole,-crit
           -xcrossfile -xalias_level=strong -Wc,-Qiselect-funcalign=32
           -xdepend -xregs=syst -xsfpcnst -Wc,-Qgsched-trace_spec_load=1 -xsafe=mem -l12amm -lprism32

```

(for Parallelnavi 1.0.2):

fdo_pre0=rm -rf `pwd`/*.fbk

PASS1=-Kpg

PASS2=-Kpu=\$(EXEBASE).fbk

181.mcf: -Kfast_GP=2,GREG,eval,preex,popt,unroll=2,prefetch=4,largepage,preload -x-

254.gap: -Kfast_GP=3,popt,eval,cfunc,largepage,xi=10

300.twolf: -Kfast_GP=5,eval,GREG,popt,cfunc,staticclump,use_rodata,xi=10,largepage,bcopy,nounroll,prefetch=4

Portability:

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN

186.crafty: -DSUN

252.eon: -library=iostream

253.perlbnk: -DSPEC_CPU2000_SOLARIS

254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_CALLOC_PROTO

Note:

System Tunables: (for /etc/system)

consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,

shmsys:shminfo_shmmax=1477846784, shmsys:shminfo_shmni=1024, shmsys:shminfo_shmsegs=1024,shminfo_shmmin=1

(for /etc/opt/FJSVpnm/lpg.conf)

TSS=8192M, SHMSEGSIZE=256M

Shell Environments:

LD_LIBRARY_PATH="/usr/lib:/opt/SUNWspro/lib/v8plusb:/opt/SUNWspro/prod/lib/v8plusb:/opt/FSUNF90/lib"

LD_LIBRARY_PATH_64="/usr/lib/64:/opt/SUNWspro/lib/v9:/opt/SUNWspro/prod/lib/v9"

PRISM_HEAP=268435456

PRISM_MODE=2

ONESTEP=yes was set for all baseline and peak benchmarks.

Feedback directed optimization was used for all baseline and peak benchmarks.

All patches of Sun ONE Studio 7 posted at URL <http://access1.sun.com/sundev/sls7-patches.html>

as of date 2002/6/4 were applied: 111704-01, 111705-01, 111706-01,

111708-01, 111709-01, 111715-01, 111716-01.