



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.53 GHz, Pentium 4 processor)

SPECint2000 = 963

SPECint_base2000 = 958

SPEC license #: 13 Tested by: Intel Corporation Test date: Jul-2002 Hardware Avail: Oct-2002 Software Avail: Apr-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	133	1052	133	1053	
175.vpr	1400	230	609	230	608	
176.gcc	1100	95.9	1147	95.7	1149	
181.mcf	1800	246	731	246	731	
186.crafty	1000	102	978	103	970	
197.parser	1800	197	916	196	916	
252.eon	1300	120	1080	112	1160	
253.perlbmk	1800	157	1150	157	1150	
254.gap	1100	88.3	1246	88.3	1245	
255.vortex	1900	118	1611	119	1603	
256.bzip2	1500	196	765	195	768	
300.twolf	3000	463	648	462	649	

Hardware

CPU: Pentium 4 processor (2.53 GHz, 533 MHz bus)
CPU MHz: 2533
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 256 MB (2 128 MB PC1066-32 RDRAM non-ECC modules)
Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
Compiler: Intel C++ Compiler 6.0 Build 020321Z
Intel Fortran Compiler 6.0 Build 020321Z
Microsoft Visual C++ 6.0 SP5(for libraries)
File System: FAT32
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -QxW -Qipo -O3 +FDO

Base tuning for C++ programs: -QxW -Qipo -GX -GR

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -QxW -Qipo -Oa -O3 +FDO

175.vpr: -QxW -Qwp_ipo -O3 +FDO

176.gcc: -QxW -Qipo -O3 +FDO

181.mcf: -QxW -Qipo -O3 +FDO

186.crafty: -QxW -Qipo -Oa -O3 +FDO

197.parser: -QxW -Qipo -O3 +FDO

252.eon: -QxW -Qipo -O3 +FDO

253.perlbmk: -QxW -Qipo -O3 +FDO

254.gap: -QxW -Qipo -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 10/2002:

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.53 GHz, Pentium 4 processor)

SPECint2000 = 963

SPECint_base2000 = 958

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2002 | Hardware Avail: Oct-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 533 MHz