



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL40p (2.8GHz, Intel Xeon MP)

SPECfp\_rate2000 = 22.8  
SPECfp\_rate\_base2000 = 22.1

SPEC license #: 3 | Test date: Sep-2003 | Hardware Avail: Jul-2003 | Software Avail: Jun-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	225	33.0	4	223	33.3
171.swim	4	1211	11.9	4	1212	11.9
172.mgrid	4	699	11.9	4	698	12.0
173.applu	4	940	10.4	4	942	10.3
177.mesa	4	128	50.6	4	128	50.8
178.galgel	4	208	64.6	4	207	65.0
179.art	4	538	22.4	4	484	24.9
183.quake	4	452	13.4	4	339	17.8
187.facerec	4	325	27.1	4	325	27.1
188.amp	4	296	34.5	4	297	34.4
189.lucas	4	749	12.4	4	746	12.4
191.fma3d	4	575	17.0	4	575	17.0
200.sixtrack	4	210	24.3	4	209	24.5
301.apsi	4	408	29.5	4	414	29.1

### Hardware

CPU: Intel Xeon MP (2.8GHz, 400MHz bus)  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 4 chips, 1 core/chip (Hyper-Threading disabled)  
 CPU(s) orderable: 1,2,4  
 Parallel: No  
 Primary Cache: 12K micro-ops I + 8KBD on chip  
 Secondary Cache: 512KB(I+D) on chip  
 L3 Cache: 2048KB(I+D) on chip  
 Other Cache: N/A  
 Memory: 2x512MB PC2100  
 Disk Subsystem: 2x36.4GB 15K Ultra320 SCSI  
 Other Hardware:

### Software

Operating System: Windows 2000 Advanced Server (Build 2195 SP3)  
 Compiler: Intel C++ Compiler 7.1 Build 20030813Z  
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
 Intel Fortran Compiler 7.1 build 20030813Z  
 MicroQuill Smartheap Library 7.0  
 File System: NTFS  
 System State: Hyperthreading disabled in BIOS

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning: -QxW -Qipo -O3 +FDO ONESTEP=yes
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW +FDO ONESTEP=yes
171.swim: -Qipo -QxW -O3 +FDO ONESTEP=yes
172.mgrid: -Qipo -QaxW -O3 +FDO ONESTEP=yes
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO ONESTEP=yes
177.mesa: -Qipo -QxW -O3 +FDO ONESTEP=yes
178.galgel: -Qipo -QxW -O3 +FDO ONESTEP=yes
179.art: -Qipo -Oa -Qunroll4 -Zp4 ONESTEP=yes
183.quake: -Qipo -QxW -Oa -Qrcd +FDO shlw32M.lib ONESTEP=yes
187.facerec: -Qipo -QaxW -O3 -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes
188.amp: -QxW -Oa ONESTEP=yes
189.lucas: -Qipo -QaxW
191.fma3d: basepeak=1
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL40p (2.8GHz, Intel Xeon MP)

SPECfp\_rate2000 = 22.8  
SPECfp\_rate\_base2000 = 22.1

SPEC license #: 3 | Test by: Hewlett-Packard Company, Houston TX | Test date: Sep-2003 | Hardware Avail: Jul-2003 | Software Avail: Jun-2003

## Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO ONESTEP=yes  
301.apsi: -Qipo -QxW -O3 +FDO ONESTEP=yes