



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation


## SGI

SGI Altix 3700 Bx2 (1600MHz 9M L3, Itanium 2)

SPECfp\_rate2000 = --

SPECfp\_rate\_base2000 = 206

SPEC license #: 4 | Tested by: SGI | Test date: Oct-2004 | Hardware Avail: Nov-2004 | Software Avail: Nov-2004



### Hardware

CPU: Intel Itanium 2  
 CPU MHz: 1600  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 8 chips, 1 core/chip  
 CPU(s) orderable: 16-256  
 Parallel: No  
 Primary Cache: 16KBI + 16KBD on chip, per core  
 Secondary Cache: 256KB (I+D) on chip, per core  
 L3 Cache: 9.0MB (I+D) on chip, per core  
 Other Cache: N/A  
 Memory: 32 GB (1GB PC2700 DIMMS)  
 Disk Subsystem: 16 x 73 GB FibreChannel (Seagate Cheetah 15k rpm)  
 Other Hardware: None

### Software

Operating System: SGI ProPack(TM) v3.0 Service Pack 1  
 Compiler: Intel(R) Fortran Compiler for Linux 8.1 (Build 20041021)  
 Intel(R) C++ Compiler for Linux 8.1 (Build 20041021)  
 File System: xfs  
 System State: Single-user

## Notes/Tuning Information

+FDO: PASS1=-prof\_gen PASS2=-prof\_use

Baseline optimization flags:

C programs: -fast -ansi\_alias -IPF\_fp\_relaxed +FDO  
 Fortran programs: -fast -IPF\_fp\_relaxed +FDO

Portability Flags:

178.galgel: -FI

Extra CPUs were disabled at firmware.  
 Processes were bound to CPUs using dplace.