



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SuperMicro
X6DHP-8G2 (3.6GHz, Intel Xeon)

SPECfp2000 = 1497

SPECfp_base2000 = 1473

SPEC license #01176 Tested by: SuperMicro Inc., San Jose, CA Test date: Oct-2004 Hardware Avail: Oct-2004 Software Avail: Dec-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	69.3	2310	69.3	2309	[Bar chart showing ratio 2309]			
171.swim	3100	138	2239	138	2239	[Bar chart showing ratio 2239]			
172.mgrid	1800	133	1351	133	1351	[Bar chart showing ratio 1351]			
173.applu	2100	150	1397	146	1440	[Bar chart showing ratio 1440]			
177.mesa	1400	88.9	1575	89.1	1572	[Bar chart showing ratio 1572]			
178.galgel	2900	128	2272	128	2271	[Bar chart showing ratio 2271]			
179.art	2600	257	1013	255	1018	[Bar chart showing ratio 1018]			
183.earth	1300	77.5	1676	63.2	2058	[Bar chart showing ratio 2058]			
187.facerec	1900	103	1843	104	1831	[Bar chart showing ratio 1831]			
188.ammmp	2200	223	987	223	987	[Bar chart showing ratio 987]			
189.lucas	2000	99.7	2007	100	1993	[Bar chart showing ratio 1993]			
191.fma3d	2100	149	1410	149	1410	[Bar chart showing ratio 1410]			
200.sixtrack	1100	170	646	170	646	[Bar chart showing ratio 646]			
301.apsi	2600	226	1149	226	1149	[Bar chart showing ratio 1149]			

Hardware

CPU: Intel Xeon (3.6GHz, 1MB L2, 800MHz bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (HT Technology Enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB, PC2-3200, CL3
Disk Subsystem: 1x36GB SCSI H.D.
Other Hardware:

Software

Operating System: Windows Server 2003 Standard (Build 3790)
Compiler: Intel C++ Compiler 8.0 Build 20031211Z
Intel Fortran Compiler 8.0 build 20040125Z
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use (-QxP not used in PASS1 to enable cross-compilation)
Base tuning Base tuning: -QxP -fast -Qansi_alias +FDO
Portability flags:
 178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -QxP -fast -Qansi_alias +FDO ONESTEP=yes
171.swim: -QxP -fast -f77rtl +FDO ONESTEP=yes
172.mgrid: -QxP -fast -Qansi_alias +FDO ONESTEP=yes
173.applu: -QxP -fast -Qscalar_rep- -Qauto -f77rtl +FDO ONESTEP=yes
177.mesa: -QxP -fast +FDO ONESTEP=yes
178.galgel: -QxP -fast +FDO ONESTEP=yes
179.art: -fast -Oa -Qunroll4 -Zp4 ONESTEP=yes
183.earth: -QxP -fast -Oa -Qrcd +FDO shlw32M.lib ONESTEP=yes
187.facerec: -QaxN -fast -Qunroll1 -Qscalar_rep- -fpp +FDO ONESTEP=yes
188.ammmp: basepeak=1
189.lucas: -QaxN-fast
191.fma3d: basepeak=1
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SuperMicro
X6DHP-8G2 (3.6GHz, Intel Xeon)

SPECfp2000 =	1497
SPECfp_base2000 =	1473

SPEC license #01176 | Tested by: SuperMicro Inc., San Jose, CA | Test date: Oct-2004 | Hardware Avail: Oct-2004 | Software Avail: Dec-2003

Notes/Tuning Information (Continued)

```
200.sixtrack: -QxP -fast +FDO
301.apsi:     -QxP -fast -f77rtl +FDO ONESTEP=yes
```