



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Advanced Micro Devices

TYAN Thunder K8QSD Pro (S4882-D), AMD Opteron (TM) 254

SPECfp\_rate2000 = 51.0

SPECfp\_rate\_base2000 = 47.0

SPEC license #: 49 Tested by: AMD, Austin, TX Test date: Aug-2005 Hardware Avail: Aug-2005 Software Avail: Aug-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	53.8	68.9	2	50.9	72.9
171.swim	2	130	55.5	2	124	58.0
172.mgrid	2	99.6	41.9	2	91.7	45.5
173.applu	2	96.8	50.3	2	87.8	55.5
177.mesa	2	65.0	50.0	2	60.7	53.5
178.galgel	2	87.8	76.6	2	79.5	84.6
179.art	2	97.9	61.6	2	70.5	85.6
183.quake	2	77.0	39.2	2	69.4	43.5
187.facerec	2	77.3	57.1	2	72.9	60.5
188.amp	2	139	36.7	2	128	39.7
189.lucas	2	92.5	50.2	2	92.5	50.2
191.fma3d	2	122	39.9	2	121	40.3
200.sixtrack	2	123	20.7	2	117	21.9
301.apsi	2	151	40.0	2	144	41.8

### Hardware

CPU: AMD Opteron (TM) 254  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip  
 CPU(s) orderable: 1-2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD on chip  
 Secondary Cache: 1024KB (I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8x512 MB, DDR400 ECC Reg CL2.5  
 Disk Subsystem: SATA, Western Digital WD740GD, 74GB 10000 rpm  
 Other Hardware: None

### Software

Operating System: SuSE Linux Enterprise Server 9 SP2 for AMD64  
 Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.1  
 File System: Linux/ext3  
 System State: Multi-user, run level 3

## Notes/Tuning Information

Tested by AMD

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML means -L/opt/acml2.5.1/pathscale64/lib -lacml,
           which causes linking with AMD Core Math Library V2.5.1
```

### Baseline optimization

```
C programs: -Ofast -WOPT:mem_opnds=on +FDO
Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on +FDO
Portability Flags:
178.galgel: -fixedform
```

### Peak Tuning:

```
168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
             -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3
             -IPA:linear=on:plimit=50000:callee_limit=5000
             -INLINE:aggressive=on
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

TYAN Thunder K8QSD Pro (S4882-D), AMD Opteron (TM) 254

SPECfp\_rate2000 = 51.0

SPECfp\_rate\_base2000 = 47.0

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Aug-2005 | Hardware Avail: Aug-2005 | Software Avail: Aug-2005

## Notes/Tuning Information (Continued)

```

171.swim:      -Ofast -LNO:fusion=2 -m3dnow
172.mgrid:    -O3 -LNO:fusion=2:blocking=off
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3
              -CG:gcm=off:cflow=off -m3dnow
173.applu:    -Ofast -CG:local_fwd_sched=on
              -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
              -OPT:ro=3 -TENV:X=3
177.mesa:     -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
178.galgel:   -Ofast -OPT:fast_complex=on +ACML
179.art:      -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32
183.quake:    -Ofast -CG:load_exe=2 -OPT:treeheight=on -WOPT:mem_opnds=on
              -m32 +FDO
187.facerec:  -Ofast -OPT:IEEE_NaN_Inf=off:ro=3 -LNO:fusion=2
              -IPA:plimit=1500 +FDO
188.ammp:     -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
              -fno-math-errno -TENV:X=4 +FDO
189.lucas:    basepeak = true
191.fma3d:    -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
              -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack:= -O3 -OPT:Ofast:Olimit=6000 -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:     -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0

```

The system under test can be built using a 13" x 16" SSI MEB case and an Enermax EPS 12 Volt ATX-6ES 660 Watt power supply.  
 All memory slots were populated with Kingston KRX3200AK2 on all CPU(s).  
 Taskset utility used to bind CPU(s) to processes.  
 Memory timings were manually set in BIOS: CL=2.5, TRCD=3, TRAS=6, TRP=3  
 BIOS Rev E.1.02