



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX220, AMD Opteron (TM) 252

SPECint2000 = **1809**
SPECint_base2000 = **1663**

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Dec-2005 | Software Avail: Mar-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	98.3	1424	98.3	1424	[Bar chart]			
175.vpr	1400	101	1393	98.1	1427	[Bar chart]			
176.gcc	1100	57.6	1910	57.9	1899	[Bar chart]			
181.mcf	1800	158	1138	132	1364	[Bar chart]			
186.crafty	1000	59.3	1686	54.3	1842	[Bar chart]			
197.parser	1800	111	1616	111	1616	[Bar chart]			
252.eon	1300	64.8	2007	45.9	2832	[Bar chart]			
253.perlbnk	1800	106	1700	97.4	1847	[Bar chart]			
254.gap	1100	60.3	1824	60.3	1824	[Bar chart]			
255.vortex	1900	72.3	2626	65.8	2888	[Bar chart]			
256.bzip2	1500	111	1353	109	1380	[Bar chart]			
300.twolf	3000	174	1722	145	2068	[Bar chart]			

Hardware

CPU: AMD Opteron (TM) 252 processor (2.60 GHz)
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB (I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x2048MB DDR-RAM PC3200R
 Disk Subsystem: Western Digital WD2500 (SATA, 7.2krpm)
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
 Compiler: Intel C++ 8.0
 Build 20040318Z (for 32-bit applications),
 Microsoft Visual Studio .Net 2003
 7.1.3088 (for libraries),
 SmartHeap Library Version 8.0
 from <http://www.microquill.com>
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast -arch:SSE2 -Oi- +FDO
 for C++ programs: -fast -GX -GR +FDO

Peak tuning flags

164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000,
 -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO shlw32M.lib
 181.mcf: -fast -QaxN +FDO shlw32M.lib
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX220, AMD Opteron (TM) 252

SPECint2000 = 1809
SPECint_base2000 = 1663

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Dec-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

```
197.parser: basepeak=yes
252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
253.perlbnk: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes shlw32M.lib
254.gap: basepeak=yes
255.vortex: -fast -arch:SSE -Oi- -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
256.bzip2: -fast -Qunroll2 shlw32M.lib
300.twolf: -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib
```

'start /b /wait /affinity' command is used to bind CPU(s) to processes

```
boot options: /Execute
              /NOPAE
              /USEPMTIMER
```

BIOS settings: Memory timing=1T

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>