



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers  
PRIMERGY BX630, AMD Opteron (TM) 252

SPECint\_rate2000 = 41.5  
SPECint\_rate\_base2000 = 38.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Jan-2006 | Software Avail: Mar-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	98.5	33.0	2	98.5	33.0
175.vpr	2	102	31.8	2	98.7	32.9
176.gcc	2	58.8	43.4	2	58.9	43.3
181.mcf	2	165	25.3	2	137	30.4
186.crafty	2	59.3	39.1	2	54.1	42.9
197.parser	2	113	37.0	2	113	37.0
252.eon	2	64.6	46.7	2	46.5	64.9
253.perlbnk	2	107	39.2	2	98.0	42.6
254.gap	2	61.5	41.5	2	61.5	41.5
255.vortex	2	73.9	59.6	2	67.1	65.7
256.bzip2	2	111	31.4	2	109	32.0
300.twolf	2	173	40.2	2	144	48.2

### Hardware

CPU: AMD Opteron (TM) 252 processor (2.60 GHz)  
CPU MHz: 2600  
FPU: Integrated  
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 64KBI + 64KBD on chip, per core  
Secondary Cache: 1024KB (I+D) on chip, per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x2048MB DDR-RAM PC3200R CL3-3-3  
Disk Subsystem: Western Digital WD2500 (SATA, 7.2krpm)  
Other Hardware: None

### Software

Operating System: Windows Server 2003 Enterprise Edition + SP1  
Compiler: Intel C++ 8.0  
Build 20040318Z (for 32-bit applications),  
Microsoft Visual Studio .Net 2003  
7.1.3088 (for libraries),  
SmartHeap Library Version 8.0  
from <http://www.microquill.com>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

+FDO: PASS1= -Qprof\_gen PASS2= -Qprof\_use

### Portability flags

176.gcc: -Dalloca=\_alloca /F10000000  
186.crafty: -DNT\_i386  
253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### Base tuning flags

for C programs: -fast -arch:SSE2 -Oi- +FDO  
for C++ programs: -fast -GX -GR +FDO

### Peak tuning flags

164.gzip: basepeak=yes  
175.vpr: -fast -arch:SSE2 -Qoption,c,-ip\_ninl\_max\_stats=2000,  
-ip\_ninl\_max\_total\_stats=4500 +FDO ONESTEP=yes  
176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO shlw32M.lib  
181.mcf: -fast -QaxN +FDO shlw32M.lib  
186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes shlw32M.lib



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers  
PRIMERGY BX630, AMD Opteron (TM) 252

SPECint\_rate2000 = 41.5  
SPECint\_rate\_base2000 = 38.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Jan-2006 | Software Avail: Mar-2004

## Notes/Tuning Information (Continued)

```
197.parser: basepeak=yes
252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
253.perlbnk: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes shlw32M.lib
254.gap: basepeak=yes
255.vortex: -fast -arch:SSE -Oi- -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
256.bzip2: -fast -Qunroll2 shlw32M.lib
300.twolf: -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib
```

'start /b /wait /affinity' command is used to bind CPU(s) to processes

```
boot options: /Execute
              /USEPMTIMER
BIOS settings: Memory Timing: 1T
              DRAM Bank Interleave=AUTO
```

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>