



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Ultra 40

SPECint_rate2000 = 71.2
SPECint_rate_base2000 = 66.3

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Feb-2006 | Hardware Avail: Jan-2006 | Software Avail: Nov-2005

| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|-------------|-------------|--------------|------------|--------|---------|-------|
| 164.gzip | 4 | 110 | 58.8 | 4 | 108 | 59.9 |
| 175.vpr | 4 | 112 | 57.9 | 4 | 112 | 58.2 |
| 176.gcc | 4 | 72.4 | 70.5 | 4 | 71.7 | 71.2 |
| 181.mcf | 4 | 217 | 38.6 | 4 | 217 | 38.5 |
| 186.crafty | 4 | 68.8 | 67.4 | 4 | 47.4 | 98.0 |
| 197.parser | 4 | 139 | 60.0 | 4 | 144 | 58.0 |
| 252.eon | 4 | 56.3 | 107 | 4 | 50.7 | 119 |
| 253.perlbnk | 4 | 114 | 73.4 | 4 | 107 | 78.1 |
| 254.gap | 4 | 87.6 | 58.2 | 4 | 82.4 | 62.0 |
| 255.vortex | 4 | 88.9 | 99.1 | 4 | 71.5 | 123 |
| 256.bzip2 | 4 | 122 | 56.9 | 4 | 122 | 57.0 |
| 300.twolf | 4 | 186 | 74.9 | 4 | 179 | 77.6 |

| Hardware | | Software | |
|-------------------|---------------------------------------------------|-------------------|---------------------|
| CPU: | AMD Opteron (TM) 280 | Operating System: | Solaris 10 3/05 HW2 |
| CPU MHz: | 2400 | Compiler: | Sun Studio 11 |
| FPU: | Integrated | File System: | ufs |
| CPU(s) enabled: | 4 cores, 2 chips, 2 cores/chip | System State: | Multi-user |
| CPU(s) orderable: | 1,2 (order by # of chips) | | |
| Parallel: | No | | |
| Primary Cache: | 64KBI + 64KBD (on chip) per core | | |
| Secondary Cache: | 1024KB (I+D) (on chip) per core | | |
| L3 Cache: | N/A | | |
| Other Cache: | N/A | | |
| Memory: | 16GB (8x2GB, PC3200 CL3 DDR ECC Registered SDRAM) | | |
| Disk Subsystem: | SATA,250GB,7200 RPM | | |
| Other Hardware: | None | | |

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC

FDO: PASS1= -xprofile=collect:./feedback PASS2= -xprofile=use:./feedback
fdo_pre0: rm -rf ./feedback.profile

Integer base flags:

Base tuning for C programs : -fast -xcrossfile -xalias_level=std +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -xcrossfile -xarch=amd64 +FDO ONESTEP=yes

Integer peak flags:

ONESTEP=yes +FDO for all benchmarks

```

164.gzip:      -fast -xpagesize=2m -xcrossfile -M /usr/lib/ld/map.bssalign
175.vpr:      -fast -xpagesize=2m -W2,-Ainline:inc=200:cs=500 -M /usr/lib/ld/map.bssalign -lmopt -lm
176.gcc:      -fast -xipo=2 -Wd,-iropt-prof -xalias_level=strong -xrestrict
181.mcf:      -fast -xpagesize=2m -xcrossfile -M /usr/lib/ld/map.bssalign
186.crafty:   -fast -xrestrict -xipo=2 -xprefetch -xarch=amd64 -xpagesize=2m
              -M /usr/lib/ld/map.bssalign -Wd,-iropt-prof -W2,-Ashort_ldst:ldld

```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Ultra 40

SPECint_rate2000 = 71.2
SPECint_rate_base2000 = 66.3

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Feb-2006 | Hardware Avail: Jan-2006 | Software Avail: Nov-2005

Notes/Tuning Information (Continued)

```

-W2,-Ainline:rs=50
197.parser: -fast -xpagesize=2m -xipo=2 -W2,-Ainline:inc=200:cs=500 -M /usr/lib/ld/map.bssalign
252.eon:     -fast -xipo=2 -qoption CC -iropt-prof -xvector -qoption iropt -Abcopy -xalias_level
           -xarch=amd64 -xrestrict -Qoption ube -xcallee=yes -xregs=frameptr
253.perlbnk: -fast -xcrossfile -M /usr/lib/ld/map.bssalign -lbsdmalloc
254.gap:     -fast -xipo=2 -Wd,-iropt-prof -xvector -W2,-Abcopy -lbsdmalloc -xprefetch
           -W2,-Ainline:cp=5:rs=1300:irs=3300:inc=100 -W2,-Arestrict_g
255.vortex: -fast -xipo=2 -Wd,-iropt-prof -lbsdmalloc -xrestrict -xprefetch -M /usr/lib/ld/map.bssalign
256.bzip2:  -fast -xpagesize=2m -xcrossfile -xarch=sse2 -Xc -M /usr/lib/ld/map.bssalign -lbsdmalloc
300.twolf:   -fast -xipo=2 -Wd,-iropt-prof -xrestrict -M /usr/lib/ld/map.bssalign

```

Portability:

```

186.crafty (base): -DSOLARIS_X86
186.crafty (peak): -DSOLARIS_X64
252.eon:          -DSPEC_CPU2000_LP64 -DUSE_STRERROR
253.perlbnk:     -DSPEC_CPU2000_SOLARIS_X86
254.gap:         -DSYS_IS_USG -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

```

Shell Environments:

Stack size set to unlimited via "ulimit -s unlimited"

Processes were bound to CPUs using submit=pbind

Default BIOS setting was used