



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL45p (AMD Opteron (TM) 885)

SPECint_rate2000 = 79.3
SPECint_rate_base2000 = 74.7

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Mar-2006 Hardware Avail: Mar-2006 Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	99.6	65.2	4	99.6	65.2
175.vpr	4	108	60.4	4	104	62.7
176.gcc	4	60.2	84.8	4	59.5	85.8
181.mcf	4	219	38.2	4	173	48.3
186.crafty	4	58.9	78.8	4	53.5	86.7
197.parser	4	114	73.0	4	114	73.2
252.eon	4	50.3	120	4	45.9	131
253.perlbnk	4	104	79.9	4	104	79.9
254.gap	4	64.3	79.4	4	64.3	79.4
255.vortex	4	74.4	118	4	74.0	119
256.bzip2	4	119	58.3	4	117	59.3
300.twolf	4	177	78.8	4	143	97.3

Hardware

CPU: AMD Opteron (TM) 885
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2,4
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB(I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x2048MB PC3200 CL3.0
 Disk Subsystem: 1x72.8GB 15K Ultra320 SCSI
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
 Compiler: Intel C++ Compiler 8.0 Build 20040318Z
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -GX -GR +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
 164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
 181.mcf: -fast -QaxN +FDO ONESTEP=yes
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
 197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
 252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 253.perlbnk: basepeak=yes
 254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL45p (AMD Opteron (TM) 885)

SPECint_rate2000 = 79.3
SPECint_rate_base2000 = 74.7

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Mar-2006 Hardware Avail: Mar-2006 Software Avail: Nov-2005

Notes/Tuning Information (Continued)

```
255.vortex:      -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
                  -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO shlw32M.lib ONESTEP=yes
256.bzip2:       -fast -Qunroll2
300.twolf:       -fast -arch:SSE2 -Qansi_alias +FDO shlw32M.lib ONESTEP=yes
```

BIOS Configuration Notes
Node Interleaving Disabled

Other Configuration Notes
The start /b /wait /affinity command is used to bind CPU(s) to processes.