



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant DL580 G4 (3.0GHz, Intel Xeon processor 7041)

SPECfp2000 = **1588**  
SPECfp\_base2000 = **1524**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jun-2006 Hardware Avail: May-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	61.3	2610	61.3	2610
171.swim	3100	157	1971	153	2021
172.mgrid	1800	136	1327	140	1286
173.applu	2100	156	1343	134	1569
177.mesa	1400	94.3	1484	87.6	1598
178.galgel	2900	124	2332	124	2332
179.art	2600	56.4	4613	56.4	4613
183.earth	1300	86.2	1509	68.3	1903
187.facerec	1900	150	1270	129	1478
188.amp	2200	204	1080	204	1080
189.lucas	2000	154	1303	154	1297
191.fma3d	2100	153	1371	153	1371
200.sixtrack	1100	188	585	188	585
301.apsi	2600	226	1151	232	1119

### Hardware

CPU: Intel Xeon processor 7041 (3.0GHz, 2x2MB L2, 800MHz bus)  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)  
 CPU(s) orderable: 1,2,4  
 Parallel: No  
 Primary Cache: 12K micro-ops I + 16KBD (on chip) per core  
 Secondary Cache: 2048KB(I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 16x2048MB PC2-3200 ECC Dual-rank  
 Disk Subsystem: 1x36GB 10K SAS  
 Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP 3  
 SuSE kernel 2.6.5-7.244-default  
 Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
 Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
 PathScale EKOPath(TM) Compiler Suite, Release 2.4  
 File System: ext2  
 System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch Ahead=5
-OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
-LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
-OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL580 G4 (3.0GHz, Intel Xeon processor 7041)

SPECfp2000 = 1588  
SPECfp\_base2000 = 1524

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jun-2006 Hardware Avail: May-2006 Software Avail: May-2006

## Notes/Tuning Information (Continued)

```
177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art: basepeak=1
183.equake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
            -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t
188.ammp: basepeak=1
189.lucas: ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
200.sixtrack: basepeak=1
301.apsi: pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t
```

### BIOS Configuration Notes

Hyper-Threading Technology disabled  
Adjacent Sector Prefetch disabled