



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM IntelliStation POWER 285 Workstation (2100 MHz, 1 CPU)

SPECint2000 = 1747

SPECint_base2000 = 1670

SPEC license #: 11 | Tested by: IBM Austin | Test date: Jun-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	148	949	142	984	
175.vpr	1400	93.0	1506	93.0	1506	
176.gcc	1100	57.2	1924	57.2	1924	
181.mcf	1800	49.2	3661	48.1	3740	
186.crafty	1000	74.9	1336	62.0	1613	
197.parser	1800	123	1466	121	1489	
252.eon	1300	70.9	1835	70.8	1836	
253.perlbmk	1800	160	1122	141	1273	
254.gap	1100	75.1	1464	74.5	1477	
255.vortex	1900	70.0	2714	66.5	2858	
256.bzip2	1500	95.2	1575	90.1	1666	
300.twolf	3000	162	1849	156	1923	

Hardware

CPU: POWER5+
 CPU MHz: 2100
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (SMT off)
 CPU(s) orderable: 1,2 core
 Parallel: No
 Primary Cache: 64 KB I + 32 KB D on chip per core
 Secondary Cache: 1920 KB I+D on chip per chip
 L3 Cache: 36 MB I+D off chip per chip, 1 chip per SUT
 Other Cache: None
 Memory: 4 GB (4x1 GB)
 Disk Subsystem: 1x73GB SCSI, 15K RPM
 Other Hardware: None

Software

Operating System: AIX 5L V5.3
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX
 XL Fortran Enterprise Edition Version 10.1 for AIX
 Other Software: ESSL 4.2.0.4
 File System: AIX/JFS2
 System State: Multi-user

Notes/Tuning Information

Portability Flags:

```
176.gcc: -ma -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DAIX
253.perlbmk: -DSPEC_CPU2000_AIX
254.gap: -DSYS_IS_BSD -DSYS_STRING_H
          -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
300.twolf: -DHAVE_SIGNED_CHAR
```

Base Optimization Flags:

```
C: -qpdf1/pdf2
   -O5 -blpdata -D_ILS_MACROS
C++: -qpdf1/pdf2
      -O4 -qalign=natural
```

Peak Optimization Flags

```
164.gzip: -qpdf1/pdf2
          -O4 -qfdpr -blpdata
          fdpr -q -O3
175.vpr: basepeak=1
176.gcc: basepeak=1
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM IntelliStation POWER 285 Workstation (2100 MHz, 1 CPU)

SPECint2000 = 1747

SPECint_base2000 = 1670

SPEC license #: 11 | Tested by: IBM Austin | Test date: Jun-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

Notes/Tuning Information (Continued)

```

181.mcf:      -qpdf1/pdf2
              -O5 -blpdata -qalign=natural -qhot=arraypad -qfdpr -Q -qmaxmem=-1
              fdpr -q -O3
186.crafty:  -qpdf1/pdf2
              -O4 -qalign=natural -q64 -lhmu -blpdata
197.parser:  -qpdf1/pdf2
              -O4 -qfdpr -D_ILS_MACROS -blpdata
              fdpr -q -O3
252.eon:     -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural
253.perlbnk: -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata -lhmu
254.gap:     -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
255.vortex:  -qpdf1/pdf2
              -O4 -qfdpr -lhmu -blpdata
              fdpr -q -O3
256.bzip2:   -qpdf1/pdf2
              -O5 -qfdpr -blpdata
              fdpr -q -O3
300.twolf:   -O5 -qfdpr -blpdata
              fdpr -q -O3

```

The installed OS level is AIX 5L for POWER Version 5.3 with the 5300-05 Recommended Technology Level.
 The installed C/C++ compiler is XL C/C++ Enterprise Edition Version 8.0 for AIX with the March 2006 PTF.
 The installed Fortran copiler is XL Fortran Enterprise Edition Version 10.1 with the May 2006 AIX PTF.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

SUT: Acronym for "System Under Test"

PTF: IBM identifier for "Program Fix Level"

```

Extended C:   IBM XL C for AIX invoked as cc
ANSI C89:     IBM XL C for AIX invoked as xlc
C++:         IBM XL C for AIX invoked as xlc

```

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=128 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
bosboot -aD
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = bindprocessor \${$} \${SPECUSERNUM}; $command
```

The "bindprocessor" AIX command binds a process to a CPU core.

One core was deconfigured and SMT disabled using the AIX commands

```

smtctl -m off -w boot
bosboot -aD
shutdown -rF
drmgr -r -c cpu

```