



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 G2 (AMD Opteron (TM) 2218)

SPECfp2000 = 1945
SPECfp_base2000 = 1766

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Sep-2006 Software Avail: Apr-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	58.5	2734	58.5	2734	
171.swim	3100	124	2504	122	2549	
172.mgrid	1800	111	1628	111	1628	
173.applu	2100	141	1485	124	1692	
177.mesa	1400	138	1015	68.8	2035	
178.galgel	2900	99.3	2921	90.9	3190	
179.art	2600	58.6	4439	58.6	4436	
183.quake	1300	78.6	1654	78.6	1654	
187.facerec	1900	95.8	1984	101	1880	
188.amp	2200	189	1162	158	1395	
189.lucas	2000	109	1843	91.1	2195	
191.fma3d	2100	133	1584	118	1778	
200.sixtrack	1100	140	787	140	787	
301.apsi	2600	173	1505	173	1505	

Hardware

CPU: AMD Opteron (TM) 2218
CPU MHz: 2600
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 64 KB I + 64 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8 GB (4x2048 MB PC2-5300P CL5.0)
Disk Subsystem: 1x36 GB 10 K SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (version 9.1 Build 20060323Z)
Intel Fortran Compiler for 32-bit applications, (version 9.1 build 20060323Z)
PGI Fortran compiler 6.0-8 for Windows XP (32-bit)
PGI C compiler 6.0-8 for Windows XP (32-bit)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
AMD Core Math Library V3.5.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use (Intel compiler)
+FDO*: PASS1=-Mpfi PASS2=-Mpfo (PGI compiler)
+ACML is linking with AMD Core Math Library V3.5.0
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran compiler, pgcc is the PGI C compiler.
Base tuning for C programs: pgcc -fastsse -Mipa=fast,inline
Base tuning for FORTRAN programs: pgf90 -fastsse -Mipa=fast,inline +FDO* ONESTEP=1
Portability flags:
178.galgel: -Mfixed
Peak tuning:
168.wupwise: pgf90 basepeak=yes
171.swim: ifort -Qipo -O3 -QaxN -QxW +FDO -Qunroll0 ONESTEP=1
172.mgrid: pgf90 basepeak=yes
173.applu: ifort -Qipo -O3 -QaxN -QxW +FDO -auto ONESTEP=1
177.mesa: icl -Qipo -arch:SSE2 +FDO -Qunroll1 -Qansi_alias ONESTEP=1
-Qoption,c,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
178.galgel: pgf90 -fastsse -Mipa=fast,safe RM_SOURCES=lapak.f90 -Munix +ACML ONESTEP=1
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 G2 (AMD Opteron (TM) 2218)

SPECfp2000 = 1945
SPECfp_base2000 = 1766

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Apr-2006

Notes/Tuning Information (Continued)

```

179.art:          pgcc -fastsse -Mipa=fast,inline
183.quake:       icl  basepeak=yes
187.facerec:     ifort -Qipo          -QxW +FDO -Qunroll3 ONESTEP=1
                  -Qoption,f,-ip_ninl_max_stats=2500,-ip_ninl_max_total_stats=7000
188.ampp:        icl  -Oa -arch:SSE2 -Zp4          -Qansi_alias ONESTEP=1
189.lucas:       ifort -Qipo          -QxW          -Qunroll1 ONESTEP=1
191.fma3d:       ifort -Qipo          -QaxN -QxW +FDO -Qansi-alias- ONESTEP=1
200.sixtrack:    pgf90 basepeak=yes
301.apsi:        pgf90 basepeak=yes

```

BIOS Configuration Notes
Node Interleaving is Disabled
Other Configuration Notes