



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL685c (AMD Opteron (TM) 8218)

SPECint_rate2000 = 162
SPECint_rate_base2000 = 150

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Nov-2006 Software Avail: Apr-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	99.2	131	8	99.2	131
175.vpr	8	108	120	8	107	122
176.gcc	8	60.5	169	8	62.0	165
181.mcf	8	206	81.2	8	173	96.4
186.crafty	8	58.5	159	8	52.3	178
197.parser	8	116	143	8	118	142
252.eon	8	52.0	232	8	39.7	304
253.perlbnk	8	98.6	169	8	98.6	169
254.gap	8	62.8	163	8	62.8	163
255.vortex	8	77.3	228	8	69.7	253
256.bzip2	8	120	116	8	115	121
300.twolf	8	179	156	8	141	197

Hardware

CPU: AMD Opteron (TM) 8218
CPU MHz: 2600
FPU: Integrated
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip
CPU(s) orderable: 2,4 chips
Parallel: No
Primary Cache: 64 KB I + 64 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: N/A
Other Cache: N/A
Memory: 32 GB (16x2 GB PC2-5300P CL5.0)
Disk Subsystem: 1x36 GB 10 K SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (version 9.1 Build 20060323Z) Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -Qcxx_features -arch:SSE2 +FDO ONESTEP=yes
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
-Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
181.mcf: -O3 -Qipo -QaxN +FDO ONESTEP=yes shlw32M.lib
186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
-Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
253.perlbnk: basepeak=yes
254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL685c (AMD Opteron (TM) 8218)

SPECint_rate2000 = 162
SPECint_rate_base2000 = 150

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Nov-2006 Software Avail: Apr-2006

Notes/Tuning Information (Continued)

```
255.vortex: -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
            -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
256.bzip2:  -O3 -Qipo -QaxN -Qunroll2 shlw32M.lib
300.twolf:  -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib
```

BIOS Configuration Notes
Node Interleaving Disabled

Other Configuration Notes
The start /b /wait /affinity command is used to bind CPU(s) to processes.