



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL365 (AMD Opteron (TM) 2218)

SPECint_rate2000 = 42.4
SPECint_rate_base2000 = 39.2

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Nov-2006 Software Avail: Apr-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	97.3	33.4	2	97.3	33.4
175.vpr	2	103	31.6	2	102	32.0
176.gcc	2	56.3	45.4	2	57.2	44.6
181.mcf	2	180	23.2	2	146	28.6
186.crafty	2	58.7	39.5	2	52.2	44.5
197.parser	2	111	37.5	2	112	37.1
252.eon	2	52.1	57.9	2	39.8	75.8
253.perlbnk	2	94.7	44.1	2	94.7	44.1
254.gap	2	59.4	43.0	2	59.4	43.0
255.vortex	2	72.0	61.2	2	65.7	67.1
256.bzip2	2	115	30.3	2	110	31.7
300.twolf	2	175	39.9	2	142	49.0

Hardware

CPU: AMD Opteron (TM) 2218
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 GB (4x2 GB PC2-5300P CL5.0)
 Disk Subsystem: 1x36 GB 10 K SAS
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
 Compiler: Intel C++ Compiler for 32-bit applications, (version 9.1 Build 20060323Z)
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -Qcxx_features -arch:SSE2 +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
 164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
 181.mcf: -O3 -Qipo -QaxN +FDO ONESTEP=yes shlw32M.lib
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
 197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
 252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 253.perlbnk: basepeak=yes
 254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL365 (AMD Opteron (TM) 2218)

SPECint_rate2000 = 42.4
SPECint_rate_base2000 = 39.2

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Nov-2006 Software Avail: Apr-2006

Notes/Tuning Information (Continued)

```
255.vortex: -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000  
           -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib  
256.bzip2:  -O3 -Qipo -QaxN -Qunroll2 shlw32M.lib  
300.twolf:  -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib
```

BIOS Configuration Notes
Node Interleaving Disabled

Other Configuration Notes
The start /b /wait /affinity command is used to bind CPU(s) to processes.