



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itaotec

Servidor Itaotec LX201 (Intel Xeon 5130 processor, 2.00GHz)

SPECint_rate2000 = 42.8

SPECint_rate_base2000 = 42.8

SPEC license #: 9001 | Tested by: Itaotec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	2	115	28.2	2	115	28.2
175.vpr	2	106	30.6	2	106	30.6
176.gcc	2	56.8	44.9	2	56.8	44.9
181.mcf	2	104	40.1	2	104	40.1
186.crafy	2	54.7	42.4	2	54.7	42.4
197.parser	2	118	35.4	2	118	35.4
252.eon	2	50.5	59.8	2	50.5	59.8
253.perlbnk	2	79.7	52.4	2	79.7	52.4
254.gap	2	58.7	43.5	2	58.7	43.5
255.vortex	2	61.5	71.7	2	61.5	71.7
256.bzip2	2	111	31.3	2	111	31.3
300.twolf	2	132	52.7	2	132	52.7

Hardware

CPU: Intel Xeon 5130 processor (2.00 GHz, 4MB L2 shared, 1333 MHz system bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4096KB(I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 4x1024MB + 4x512MB FB-DIMM DDR2 SDRAM ECC CL5 667MHz
Disk Subsystem: 1 x 200GB Serial ATA 7200 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio .NET 7.0.9466 (for libraries),
MicroQuill SmartHeap for SMP Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for C programs: -fast -QxP +FDO shlSMPMt.lib
for C++ programs: -fast -Qcxx_features +FDO

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>