



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3200 (2.13 GHz Xeon 3050, 4MB L2 Cache)

SPECfp_rate2000 = --

SPECfp_rate_base2000 = 36.9

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Oct-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	56.4	65.8			
171.swim	2	227	31.6			
172.mgrid	2	155	27.0			
173.applu	2	180	27.1			
177.mesa	2	66.8	48.6			
178.galgel	2	109	61.8			
179.art	2	92.9	64.9			
183.quake	2	69.4	43.5			
187.facerec	2	102	43.1			
188.amp	2	214	23.9			
189.lucas	2	137	33.8			
191.fma3d	2	159	30.7			
200.sixtrack	2	132	19.3			
301.apsi	2	186	32.4			

Hardware

CPU: Intel Xeon processor 3050 (2.13 GHz, 1066 MHz bus)
CPU MHz: 2133
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1 chip
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
Secondary Cache: 4096KB(I+D) on chip (per chip)
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 1024 MB ECC PC2-5300
Disk Subsystem: 73GB SAS 15K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z
Microsoft Visual Studio 2005 (for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
```