



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB8(2.66GHz, Intel Xeon X5355 processor)

SPECint2000 = 2760

SPECint_base2000 = 2755

SPEC license #01176 Tested by: Supermicro Test date: Nov-2006 Hardware Avail: Nov-2006 Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	84.3	1660	84.0	1668	
175.vpr	1400	69.7	2008	68.4	2048	
176.gcc	1100	39.1	2812	39.1	2812	
181.mcf	1800	41.7	4318	41.7	4318	
186.crafty	1000	40.5	2469	40.6	2464	
197.parser	1800	87.1	2067	87.4	2060	
252.eon	1300	37.5	3468	37.3	3490	
253.perlbmk	1800	54.8	3285	55.0	3275	
254.gap	1100	40.5	2714	40.5	2714	
255.vortex	1900	41.3	4601	41.3	4601	
256.bzip2	1500	70.5	2127	70.6	2123	
300.twolf	3000	97.9	3065	97.8	3067	

Hardware

CPU: Intel Xeon X5355 processor (2.66 GHz,1333MHz bus)
 CPU MHz: 2660
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Parallel: N/A
 Primary Cache: 32KBI + 32KBD on chip per core
 Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 X 2GB DDR2 ECC CL5 667MHz FBDIMM
 Disk Subsystem: 1 X Seagate Baeeacuda 120GB 7200 RPM
 Other Hardware: N/A

Software

Operating System: Windows Server 2003 Enterprise Edition 32-bits w/ SP1
 Compiler: Intel C++ Compiler 9.1 for 32-bit applications
 Build 20060323Z Package ID: W_CC_P_9.1.020
 Microsoft Visual Studio 2005(for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB8(2.66GHz, Intel Xeon X5355 processor)

SPECint2000 = 2760

SPECint_base2000 = 2755

SPEC license #01176 | Tested by: Supermicro | Test date: Nov-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO
300.twolf: -fast -O3 +FDO shlw32m.lib

Tested systems can be used with SC816S-R700 case,
To ensure system stability, a 500W (minimum) ATX power supply [4-pin (+12V), 8-pin (+12V) and 24-pin are required]
Product description located as of <http://www.supermicro.com/products/motherboard/Xeon1333/5000P/X7DB8.cfm>

The system bus runs at 1333 MHz

shlw32m-80.lib is the V8.0 SmartHeap library renamed to co-exist with older versions