



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor E5345, 2.33 GHz

SPECfp_rate2000 = 98.9

SPECfp_rate_base2000 = 98.9

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	129	115	8	129	115
171.swim	8	538	53.5	8	538	53.5
172.mgrid	8	337	49.5	8	337	49.5
173.applu	8	359	54.3	8	359	54.3
177.mesa	8	60.7	214	8	60.7	214
178.galgel	8	88.2	305	8	88.2	305
179.art	8	89.1	271	8	89.1	271
183.quake	8	245	49.3	8	245	49.3
187.facerec	8	136	130	8	136	130
188.amp	8	145	141	8	145	141
189.lucas	8	313	59.3	8	313	59.3
191.fma3d	8	289	67.5	8	289	67.5
200.sixtrack	8	127	80.1	8	127	80.1
301.apsi	8	241	100	8	241	100

Hardware

CPU: Intel Xeon processor E5345 (2.33 GHz, 2x4MB L2, 1333 MHz system bus)
CPU MHz: 2333
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem: Seagate ST373454SS (SAS, 15.4krpm, 73GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10
Kernel 2.6.16.21-0.8-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.1 for EM64T
Build 20060816 (for 64-bit applications)
File System: reiserfs
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
for Fortran and C programs: -fast +FDO

Peak tuning flags
same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor E5345, 2.33 GHz

SPECfp_rate2000 = 98.9

SPECfp_rate_base2000 = 98.9

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

BIOS Configuration:

Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>