



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor X5355, 2.66 GHz

SPECint\_rate2000 = 105

SPECint\_rate\_base2000 = 105

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jan-2007 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	88.0	73.8	4	88.0	73.8
175.vpr	4	84.4	77.0	4	84.4	77.0
176.gcc	4	50.7	101	4	50.7	101
181.mcf	4	98.5	84.8	4	98.5	84.8
186.crafty	4	41.1	113	4	41.1	113
197.parser	4	93.1	89.7	4	93.1	89.7
252.eon	4	37.7	160	4	37.7	160
253.perlbnk	4	58.4	143	4	58.4	143
254.gap	4	61.6	82.8	4	61.6	82.8
255.vortex	4	49.8	177	4	49.8	177
256.bzip2	4	90.5	76.9	4	90.5	76.9
300.twolf	4	98.3	142	4	98.3	142

### Hardware

CPU: Intel Xeon processor X5355 (2.66 GHz, 2x4MB L2, 1333 MHz system bus)  
CPU MHz: 2666  
FPU: Integrated  
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)  
Disk Subsystem: Seagate ST936701SS (SAS, 10 krpm, 36GB)  
Other Hardware: none

### Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)  
Compiler: Intel C++ Compiler 9.1  
Build 20060323Z (for 32-bit applications),  
Microsoft Visual Studio .Net 2003  
7.1.3088 (for libraries),  
SmartHeap Library Version 8.0  
from <http://www.microquill.com>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### Portability flags

176.gcc: -Dalloca=\_alloca /F10000000  
186.crafty: -DNT\_i386  
253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### Base tuning flags

for C programs: -fast +FDO shlw32m.lib  
for C++ programs: -fast -Qcxx\_features +FDO shlw32m.lib

### Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 1333 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY BX620 S3, Intel Xeon processor X5355, 2.66 GHz

SPECint\_rate2000 = 105

SPECint\_rate\_base2000 = 105

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jan-2007 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

BIOS Configuration:

Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>