



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R630 E1 LR
(Intel Xeon E5405, 2.00 GHz)

SPECint_rate2006 = 55.0

SPECint_rate_base2006 = 51.7

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Dec-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008



SPECint_rate_base2006 = 51.7

SPECint_rate2006 = 55.0

Hardware

CPU Name: Intel Xeon E5405
CPU Characteristics: 1333 MHz system bus
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
CPU(s) orderable: 1,2 chips (fault tolerant, see Platform Notes)
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache: None
Other Cache: None
Memory: 12 GB (6x2 GB PC2-5300F, 2 rank, CL5-5-5, ECC)
Disk Subsystem: 2x146.5 GB SAS, 15000 RPM, Software RAID Level1
Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server release 5.2 Advanced Platform, Kernel 2.6.18-92.1.13.el5 on an x86_64
Compiler: Intel C++ Compiler 11.0 for Linux Build 20081105 Package ID: l_cproc_p_11.0.074
Auto Parallel: Yes
File System: ext3
System State: Run level 3 (multi-user)
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: MicroQuill SmartHeap Library 8.1 ft Server Control Software 6.0.2-198



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R630 E1 LR
(Intel Xeon E5405, 2.00 GHz)

SPECint_rate2006 = 55.0

SPECint_rate_base2006 = 51.7

CPU2006 license: 20

Test date: Dec-2008

Test sponsor: Bull SAS

Hardware Availability: Oct-2008

Tested by: NEC Corporation

Software Availability: Nov-2008

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	696	56.2	698	56.0	694	56.3	4	599	65.3	595	65.7	594	65.8
401.bzip2	4	974	39.6	986	39.2	973	39.7	4	928	41.6	939	41.1	928	41.6
403.gcc	4	704	45.8	705	45.7	700	46.0	4	713	45.2	712	45.2	705	45.6
429.mcf	4	651	56.0	652	55.9	653	55.8	4	679	53.8	682	53.5	681	53.6
445.gobmk	4	787	53.3	788	53.2	790	53.1	4	736	57.0	738	56.8	740	56.7
456.hammer	4	707	52.8	709	52.6	710	52.5	4	547	68.2	550	67.9	551	67.7
458.sjeng	4	895	54.1	891	54.3	888	54.5	4	848	57.1	854	56.7	853	56.7
462.libquantum	4	1006	82.4	1008	82.2	1008	82.2	1	261	79.3	262	79.2	260	79.8
464.h264ref	4	1019	86.9	1018	86.9	1022	86.6	4	962	92.0	961	92.1	961	92.1
471.omnetpp	4	765	32.7	766	32.6	765	32.7	4	721	34.7	718	34.8	723	34.6
473.astar	4	868	32.4	867	32.4	873	32.2	4	762	36.9	765	36.7	761	36.9
483.xalancbmk	4	491	56.2	489	56.4	492	56.1	4	491	56.2	489	56.4	492	56.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
taskset was used to bind processes to cores except
for 462.libquantum peak

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to "physical,0"
KMP_STACKSIZE set to 64M

Platform Notes

This Express5800/320Fd-LR is a fault-tolerant server.
Two modules are installed in this server.

Each module physically has "1CPU chips,12GB memory", The total physical configuration
is "2CPU chips,24GB memory".

Using fault-tolerant lockstep technology, these two modules communicate with each other
and execute the same instructions at the same time, The operating system only sees
"1CPU chips,12GB memory" as the other components add only redundancy and do not
contribute to any performance benefit.



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R630 E1 LR
(Intel Xeon E5405, 2.00 GHz)

SPECint_rate2006 = 55.0

SPECint_rate_base2006 = 51.7

CPU2006 license: 20

Test date: Dec-2008

Test sponsor: Bull SAS

Hardware Availability: Oct-2008

Tested by: NEC Corporation

Software Availability: Nov-2008

General Notes

The NEC Express5800/320Fd-LR(Intel Xeon E5405) and the Bull NovaScale R630 E1 LR(Intel Xeon E5405, 2.00 GHz) models are electronically equivalent. The results have been measured on a NEC Express5800/320Fd-LR(Intel Xeon E5405) model.

Base Compiler Invocation

C benchmarks:
 icc

C++ benchmarks:
 icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
 -xSSE4.1 -ipo -O3 -no-prec-div -static -inline-calloc
 -opt-malloc-options=3 -opt-prefetch

C++ benchmarks:
 -xSSE4.1 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
 -L/opt/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:
 403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
 icc

401.bzip2: /opt/intel/Compiler/11.0/074/bin/intel64/icc
 -L/opt/intel/Compiler/11.0/074/ipp/em64t/lib
 -I/opt/intel/Compiler/11.0/074/ipp/em64t/include

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R630 E1 LR
(Intel Xeon E5405, 2.00 GHz)

SPECint_rate2006 = 55.0

SPECint_rate_base2006 = 51.7

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Dec-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

Peak Compiler Invocation (Continued)

```
456.hmmer: /opt/intel/Compiler/11.0/074/bin/intel64/icc
           -L/opt/intel/Compiler/11.0/074/ipp/em64t/lib
           -I/opt/intel/Compiler/11.0/074/ipp/em64t/include
```

C++ benchmarks:
icpc

Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LINUX_IA32
               401.bzip2: -DSPEC_CPU_LP64
               456.hmmer: -DSPEC_CPU_LP64
               462.libquantum: -DSPEC_CPU_LINUX
               483.xalancbmk: -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
               -no-prec-div -static -ansi-alias -opt-prefetch
               401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
               -no-prec-div -static -opt-prefetch -ansi-alias
               403.gcc: -xSSE4.1 -ipo -O3 -no-prec-div -static -inline-calloc
                         -opt-malloc-options=3
               429.mcf: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
                         -no-prec-div -static -opt-prefetch
               445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -O2 -ipo
                         -no-prec-div -ansi-alias
               456.hmmer: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll12
                         -ansi-alias
               458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
                         -no-prec-div -static -unroll14
               462.libquantum: -xSSE4.1 -ipo -O3 -no-prec-div -static
                           -opt-malloc-options=3 -parallel -par-runtime-control
                           -opt-prefetch
               464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
                           -no-prec-div -static -unroll12 -ansi-alias
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R630 E1 LR
(Intel Xeon E5405, 2.00 GHz)

SPECint_rate2006 = 55.0

SPECint_rate_base2006 = 51.7

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Dec-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

C++ benchmarks:

```
471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
             -no-prec-div -ansi-alias -opt-ra-region-strategy=block
             -Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmartheap
```

```
473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
             -no-prec-div -ansi-alias -opt-ra-region-strategy=routine
             -Wl,-z,muldefs -L/opt/SmartHeap_8.1/lib -lsmartheap
```

```
483.xalancbmk: basepeak = yes
```

Peak Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revE.html>

<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revE.xml>

<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 22:23:26 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 20 January 2009.