



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

**SPECint®\_rate2006 = 207**

PRIMERGY TX300 S5, Intel Xeon L5530, 2.40 GHz

**SPECint\_rate\_base2006 = 192**

CPU2006 license: 19


**Test date:** Jul-2009

**Test sponsor:** Fujitsu

**Hardware Availability:** Aug-2009

**Tested by:** Fujitsu

**Software Availability:** Feb-2009



## Hardware

CPU Name:	Intel Xeon L5530
CPU Characteristics:	Intel Turbo Boost Technology up to 2.67 GHz
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip
Other Cache:	None
Memory:	48 GB (12x4 GB PC3-10600R, 2 rank, CL9-9-9, ECC, see add'l detail in notes)
Disk Subsystem:	1 x SATA, 250 GB, 7200 RPM
Other Hardware:	None

## Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16.60-0.21-smp
Compiler:	Intel C++ Compiler 11.0 for Linux Build 20090131 Package ID: l_cproc_p_11.0.080
Auto Parallel:	No
File System:	ext3
System State:	Multi-User Run Level 3
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V8.1 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

**SPECint\_rate2006 = 207**

PRIMERGY TX300 S5, Intel Xeon L5530, 2.40 GHz

**SPECint\_rate\_base2006 = 192**

CPU2006 license: 19

Test date: Jul-2009

Test sponsor: Fujitsu

Hardware Availability: Aug-2009

Tested by: Fujitsu

Software Availability: Feb-2009

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	16	879	178	884	177	<b>884</b>	<b>177</b>	16	<b>748</b>	<b>209</b>	752	208	746	210
401.bzip2	16	1217	127	1223	126	<b>1219</b>	<b>127</b>	16	1145	135	1151	134	<b>1146</b>	<b>135</b>
403.gcc	16	785	164	778	166	<b>779</b>	<b>165</b>	16	<b>777</b>	<b>166</b>	774	166	781	165
429.mcf	16	672	217	669	218	<b>671</b>	<b>217</b>	8	318	230	<b>318</b>	<b>229</b>	319	229
445.gobmk	16	865	194	858	196	<b>862</b>	<b>195</b>	16	785	214	787	213	<b>786</b>	<b>214</b>
456.hmmer	16	<b>1020</b>	<b>146</b>	1021	146	1019	146	8	387	193	<b>387</b>	<b>193</b>	387	193
458.sjeng	16	1056	183	1055	184	<b>1055</b>	<b>183</b>	16	960	202	<b>959</b>	<b>202</b>	958	202
462.libquantum	16	<b>526</b>	<b>630</b>	527	629	526	630	16	<b>526</b>	<b>630</b>	527	629	526	630
464.h264ref	16	<b>1419</b>	<b>250</b>	1420	249	1415	250	16	<b>1351</b>	<b>262</b>	1355	261	1321	268
471.omnetpp	16	<b>750</b>	<b>133</b>	753	133	661	151	16	<b>750</b>	<b>133</b>	753	133	661	151
473.astar	16	883	127	<b>882</b>	<b>127</b>	881	127	16	796	141	<b>796</b>	<b>141</b>	796	141
483.xalancbmk	16	501	220	<b>501</b>	<b>220</b>	501	220	16	501	220	<b>501</b>	<b>220</b>	501	220

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

The system automatically configures the memory to run at 1066 MHz.

## General Notes

This result was measured on the PRIMERGY TX300 S5. The PRIMERGY TX300 S5 and the PRIMERGY RX300 S5 are electronically equivalent.

For information about Fujitsu please visit: <http://www.fujitsu.com>

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY TX300 S5, Intel Xeon L5530, 2.40 GHz

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

**SPECint\_rate2006 = 207**

**SPECint\_rate\_base2006 = 192**

Test date: Jul-2009

Hardware Availability: Aug-2009

Software Availability: Feb-2009

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -inline-calloc  
-opt-malloc-options=3 -opt-prefetch

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/Compiler/11.0/080/bin/intel64/icc

456.hmmr: /opt/intel/Compiler/11.0/080/bin/intel64/icc

458.sjeng: /opt/intel/Compiler/11.0/080/bin/intel64/icc

C++ benchmarks (except as noted below):

icpc

473.astar: /opt/intel/Compiler/11.0/080/bin/intel64/icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmr: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY TX300 S5, Intel Xeon L5530, 2.40 GHz

**SPECint\_rate2006 = 207**

CPU2006 license: 19

Test date: Jul-2009

Test sponsor: Fujitsu

Hardware Availability: Aug-2009

Tested by: Fujitsu

Software Availability: Feb-2009

## Peak Portability Flags (Continued)

```
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
    473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
    -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
    -prof-use(pass 2) -ansi-alias -opt-prefetch

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
    -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
    -prof-use(pass 2) -opt-prefetch -ansi-alias -auto-ilp32

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -static -inline-calloc
    -opt-malloc-options=3

429.mcf: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
    -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
    -prof-use(pass 2) -opt-prefetch

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2
    -ipo -no-prec-div -ansi-alias

456.hmmr: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll12
    -ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
    -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
    -prof-use(pass 2) -unroll14 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
    -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
    -prof-use(pass 2) -unroll12 -ansi-alias
```

C++ benchmarks:

```
471.omnetpp: basepeak = yes

473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
    -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
    -ansi-alias -opt-ra-region-strategy=routine -auto-ilp32
    -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap64
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY TX300 S5, Intel Xeon L5530, 2.40 GHz

**SPECint\_rate2006 = 207**

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Jul-2009

Hardware Availability: Aug-2009

Software Availability: Feb-2009

## Peak Optimization Flags (Continued)

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090710.14.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090710.14.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 03:39:36 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 18 August 2009.