



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

**SPECfp®2006 = 21.5**

IBM System x3250 M2 (Intel Core 2 Duo E7400)

**SPECfp\_base2006 = 20.7**

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: May-2009

Hardware Availability: Apr-2009

Software Availability: Nov-2008



## Hardware

CPU Name: Intel Core 2 Duo E7400  
CPU Characteristics: 1067 MHz system bus  
CPU MHz: 2800  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1 chip  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 3 MB I+D on chip per chip

## Software

Operating System: SuSE Linux Enterprise Server 10(x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080930 Package ID: l\_cproc\_p\_11.0.066  
Auto Parallel: Yes  
File System: ReiserFS  
System State: Run level 3 (multi-user)  
Base Pointers: 64-bit

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

IBM System x3250 M2 (Intel Core 2 Duo E7400)

**SPECfp2006 = 21.5**

CPU2006 license: 11

Test date: May-2009

Test sponsor: IBM Corporation

Hardware Availability: Apr-2009

Tested by: IBM Corporation

Software Availability: Nov-2008

L3 Cache: None  
 Other Cache: None  
 Memory: 8 GB(4 x 2 GB DDR2-6400E ECC)  
 Disk Subsystem: 1 x 250 GB SATA, 7200RPM  
 Other Hardware: None

Peak Pointers: 32/64-bit  
 Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	452	30.0	449	30.2	<b>450</b>	<b>30.2</b>	<b>451</b>	<b>30.2</b>	449	30.3	454	30.0
416.gamess	<b>948</b>	<b>20.7</b>	947	20.7	949	20.6	922	21.2	<b>918</b>	<b>21.3</b>	918	21.3
433.milc	466	19.7	<b>467</b>	<b>19.7</b>	467	19.7	469	19.6	469	19.6	<b>469</b>	<b>19.6</b>
434.zeusmp	373	24.4	373	24.4	<b>373</b>	<b>24.4</b>	373	24.4	373	24.4	<b>373</b>	<b>24.4</b>
435.gromacs	387	18.5	387	18.4	<b>387</b>	<b>18.4</b>	383	18.6	386	18.5	<b>383</b>	<b>18.6</b>
436.cactusADM	346	34.5	<b>346</b>	<b>34.5</b>	347	34.4	<b>316</b>	<b>37.8</b>	317	37.7	315	37.9
437.leslie3d	558	16.8	559	16.8	<b>558</b>	<b>16.8</b>	558	16.8	559	16.8	<b>558</b>	<b>16.8</b>
444.namd	<b>525</b>	<b>15.3</b>	525	15.3	525	15.3	528	15.2	529	15.2	<b>529</b>	<b>15.2</b>
447.dealII	406	28.2	<b>406</b>	<b>28.2</b>	406	28.2	<b>370</b>	<b>30.9</b>	<b>371</b>	<b>30.9</b>	371	30.8
450.soplex	540	15.5	541	15.4	<b>541</b>	<b>15.4</b>	506	16.5	<b>506</b>	<b>16.5</b>	507	16.4
453.povray	237	22.5	<b>236</b>	<b>22.5</b>	236	22.5	<b>192</b>	<b>27.7</b>	192	27.7	192	27.6
454.calculix	364	22.7	365	22.6	<b>365</b>	<b>22.6</b>	360	22.9	359	23.0	<b>360</b>	<b>22.9</b>
459.GemsFDTD	623	17.0	<b>623</b>	<b>17.0</b>	623	17.0	<b>622</b>	<b>17.0</b>	622	17.0	623	17.0
465.tonto	520	18.9	<b>522</b>	<b>18.9</b>	523	18.8	469	21.0	474	20.8	<b>471</b>	<b>20.9</b>
470.lbm	909	15.1	<b>908</b>	<b>15.1</b>	906	15.2	909	15.1	<b>908</b>	<b>15.1</b>	906	15.2
481.wrf	527	21.2	526	21.2	<b>526</b>	<b>21.2</b>	526	21.2	527	21.2	<b>527</b>	<b>21.2</b>
482.sphinx3	943	20.7	938	20.8	<b>942</b>	<b>20.7</b>	<b>896</b>	<b>21.7</b>	899	21.7	886	22.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

Hardware Sector Prefetch Enable and Adjacent Sector Prefetch Enable  
 OMP\_NUM\_THREADS set to number of cores  
 KMP\_AFFINITY set to "physical,0"  
 KMP\_STACKSIZE set to 200M

## Base Compiler Invocation

C benchmarks:  
 icc

C++ benchmarks:  
 icpc

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

**SPECfp2006 = 21.5**

IBM System x3250 M2 (Intel Core 2 Duo E7400)

**SPECfp\_base2006 = 20.7**

CPU2006 license: 11

Test date: May-2009

Test sponsor: IBM Corporation

Hardware Availability: Apr-2009

Tested by: IBM Corporation

Software Availability: Nov-2008

## Base Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

C++ benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Fortran benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

**SPECfp2006 = 21.5**

IBM System x3250 M2 (Intel Core 2 Duo E7400)

**SPECfp\_base2006 = 20.7**

CPU2006 license: 11

Test date: May-2009

Test sponsor: IBM Corporation

Hardware Availability: Apr-2009

Tested by: IBM Corporation

Software Availability: Nov-2008

## Peak Compiler Invocation (Continued)

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc

450.soplex: icpc -m32

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -fno-alias

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
-no-prec-div -static -fno-alias -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**IBM Corporation**

IBM System x3250 M2 (Intel Core 2 Duo E7400)

**SPECfp2006 =**

**21.5**

**SPECfp\_base2006 =**

**20.7**

**CPU2006 license:** 11

**Test date:**

May-2009

**Test sponsor:** IBM Corporation

**Hardware Availability:**

Apr-2009

**Tested by:** IBM Corporation

**Software Availability:**

Nov-2008

## Peak Optimization Flags (Continued)

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3  
 -no-prec-div -static -unroll2 -ansi-alias -scalar-rep-  
 -opt-prefetch

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3  
 -no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3  
 -no-prec-div -static -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xsse4.1 -ipo -O3 -no-prec-div -static -opt-prefetch  
 -parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3  
 -no-prec-div -static -unroll2 -Ob0 -ansi-alias  
 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3  
 -no-prec-div -static -unroll2 -Ob0 -opt-prefetch  
 -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3  
 -no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3  
 -no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3  
 -no-prec-div -static -unroll2 -opt-prefetch -parallel  
 -auto-ilp32

454.calculix: -xsse4.1 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: -xsse4.1 -ipo -O3 -no-prec-div -static -opt-prefetch  
 -parallel -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090827.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090827.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3250 M2 (Intel Core 2 Duo E7400)

**SPECfp2006 = 21.5**

**SPECfp\_base2006 = 20.7**

**CPU2006 license:** 11

**Test sponsor:** IBM Corporation

**Tested by:** IBM Corporation

**Test date:** May-2009

**Hardware Availability:** Apr-2009

**Software Availability:** Nov-2008

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Sep 23 18:18:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 2 September 2009.