



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

### SPECfp®\_rate2006 = 73.2

### Intel DH67BLB3 Motherboard (Intel Core i3-2120)

### SPECfp\_rate\_base2006 = 72.9

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2011

Hardware Availability: Mar-2011

Software Availability: Apr-2011



### Hardware

CPU Name: Intel Core i3-2120  
 CPU Characteristics:  
 CPU MHz: 3300  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Windows 7 Ultimate (64-bit)  
 Compiler: Intel C++ Compiler XE for Intel 64  
 Version 12.0.3.176 Build 20110309  
 Intel Visual Fortran Compiler XE for Intel 64  
 Version 12.0.3.176 Build 20110309  
 Microsoft Visual Studio 2008 Professional SP1  
 (for libraries)

Auto Parallel: No  
 File System: NTFS

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

SPECfp\_rate2006 = **73.2**

Intel DH67BLB3 Motherboard (Intel Core i3-2120)

SPECfp\_rate\_base2006 = **72.9**

CPU2006 license: 13

Test date: Jul-2011

Test sponsor: Intel Corporation

Hardware Availability: Mar-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

L3 Cache: 3 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 4 GB (2 x 2 GB 2Rx8 PC3-10600U-9)  
 Disk Subsystem: Seagate 1 TB SATA, 7200 RPM  
 Other Hardware: None

System State: Default  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	598	90.8	589	92.4	<b>590</b>	<b>92.0</b>	4	598	90.8	589	92.4	<b>590</b>	<b>92.0</b>
416.gamess	4	1173	66.8	1172	66.8	<b>1172</b>	<b>66.8</b>	4	1173	66.8	1172	66.8	<b>1172</b>	<b>66.8</b>
433.milc	4	392	93.6	<b>393</b>	<b>93.6</b>	393	93.6	4	392	93.6	<b>393</b>	<b>93.6</b>	393	93.6
434.zeusmp	4	495	73.6	<b>494</b>	<b>73.6</b>	493	73.6	4	495	73.6	<b>494</b>	<b>73.6</b>	493	73.6
435.gromacs	4	492	58.0	<b>492</b>	<b>58.0</b>	491	58.0	4	492	58.0	<b>492</b>	<b>58.0</b>	491	58.0
436.cactusADM	4	656	72.8	<b>656</b>	<b>72.8</b>	658	72.8	4	656	72.8	<b>656</b>	<b>72.8</b>	658	72.8
437.leslie3d	4	703	53.6	<b>704</b>	<b>53.6</b>	707	53.2	4	703	53.6	<b>704</b>	<b>53.6</b>	707	53.2
444.namd	4	<b>561</b>	<b>57.2</b>	561	57.2	561	57.2	4	<b>556</b>	<b>57.6</b>	556	57.6	556	57.6
447.dealII	4	625	73.2	<b>642</b>	<b>71.2</b>	643	71.2	4	<b>618</b>	<b>74.0</b>	610	75.2	618	74.0
450.soplex	4	<b>601</b>	<b>55.6</b>	601	55.6	601	55.6	2	333	50.0	<b>333</b>	<b>50.0</b>	333	50.0
453.povray	4	227	94.0	226	94.0	<b>227</b>	<b>94.0</b>	4	192	111	<b>191</b>	<b>112</b>	190	112
454.calculix	4	381	86.4	<b>382</b>	<b>86.4</b>	382	86.4	4	381	86.4	<b>382</b>	<b>86.4</b>	382	86.4
459.GemsFDTD	4	937	45.2	938	45.2	<b>938</b>	<b>45.2</b>	4	937	45.2	938	45.2	<b>938</b>	<b>45.2</b>
465.tonto	4	574	68.4	<b>574</b>	<b>68.4</b>	575	68.4	4	568	69.2	568	69.2	<b>568</b>	<b>69.2</b>
470.lbm	4	<b>502</b>	<b>109</b>	503	109	502	110	4	<b>502</b>	<b>109</b>	503	109	502	110
481.wrf	4	<b>444</b>	<b>100</b>	444	101	446	100	4	<b>444</b>	<b>100</b>	444	101	446	100
482.sphinx3	4	<b>1010</b>	<b>77.2</b>	1012	77.2	1009	77.2	4	1046	74.4	<b>1046</b>	<b>74.4</b>	1046	74.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
 The start command with the /affinity switch was used to bind processes to cores

## General Notes

Tested systems can be used with Shin-G ATX case,  
 PC Power and Cooling 1200W power supply

## Base Compiler Invocation

C benchmarks:  
 icl -Qvc9 -Qstd=c99

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 73.2

Intel DH67BLB3 Motherboard (Intel Core i3-2120)

SPECfp\_rate\_base2006 = 72.9

CPU2006 license: 13

Test date: Jul-2011

Test sponsor: Intel Corporation

Hardware Availability: Mar-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

## Base Compiler Invocation (Continued)

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_P64 -names:lowercase  
 416.gamess: -DSPEC\_CPU\_P64  
 433.milc: -DSPEC\_CPU\_P64  
 434.zeusmp: -DSPEC\_CPU\_P64  
 435.gromacs: -DSPEC\_CPU\_P64  
 436.cactusADM: -DSPEC\_CPU\_P64 /names:lowercase /assume:underscore  
 437.leslie3d: -DSPEC\_CPU\_P64  
 444.namd: -DSPEC\_CPU\_P64 /TP  
 447.dealII: -DSPEC\_CPU\_P64 -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
 450.soplex: -DSPEC\_CPU\_P64  
 453.povray: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WINDOWS\_ICL  
 454.calculix: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_NOZMODIFIER /names:lowercase  
 459.GemsFDTD: -DSPEC\_CPU\_P64  
 465.tonto: -DSPEC\_CPU\_P64  
 470.lbm: -DSPEC\_CPU\_P64  
 481.wrf: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WINDOWS\_ICL  
 482.sphinx3: -DSPEC\_CPU\_P64

## Base Optimization Flags

C benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F1000000000  
-link /FORCE:MULTIPLE

C++ benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qcxx-features  
-Qauto-ilp32 /F1000000000 shlw64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias /F1000000000  
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

-QxAVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F1000000000  
-link /FORCE:MULTIPLE



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 73.2

Intel DH67BLB3 Motherboard (Intel Core i3-2120)

SPECfp\_rate\_base2006 = 72.9

CPU2006 license: 13

Test date: Jul-2011

Test sponsor: Intel Corporation

Hardware Availability: Mar-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

## Peak Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: -QxAVX -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias  
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE

C++ benchmarks:

444.namd: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000 sh1W64M.lib  
-link /FORCE:MULTIPLE

447.dealII: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qunroll2 -Qansi-alias -Qscalar-rep-  
-Qauto-ilp32 /F1000000000 sh1W64M.lib  
-link /FORCE:MULTIPLE

450.soplex: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qauto-ilp32 /F1000000000 sh1W64M.lib  
-link /FORCE:MULTIPLE

453.povray: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32 /F1000000000  
sh1W64M.lib -link /FORCE:MULTIPLE

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp\_rate2006 = 73.2

Intel DH67BLB3 Motherboard (Intel Core i3-2120)

SPECfp\_rate\_base2006 = 72.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2011

Hardware Availability: Mar-2011

Software Availability: Apr-2011

## Peak Optimization Flags (Continued)

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxAVX(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000  
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.20110808.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.20110808.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Thu Jul 24 00:05:55 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 2 August 2011.