

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Hewlett-Packard Company: ProLiant DL380 G3
Red Hat: Red Hat Content Accelerator 2

SPECweb99 = 5372

Test Date: Mar-2003
Tester: Hewlett-Packard Company

Hardware Avail: May-2003 OS Avail: Nov-2002 HTTP Software Avail: Nov-2002 Sup. Software Avail: Nov-2002 SPEC license #: 3

Hardware

Vendor: Hewlett-Packard Company
Model: ProLiant DL380 G3
Processor: 3060MHz Intel Xeon
Processors: 2 cores, 2 chips, 1 core/chip (Hyper-Threading enabled)
Primary Cache: 12KB Execution and 8KB Data on chip
Secondary Cache: 512KB
Other Cache: None
Memory: 12 GB
Disk Subsystem: 6x36.4GB SCSI
Disk Controllers: HP Smart Array 5312 Controller
Other Hardware: Anritsu MultiFlow 5128 Switch

Software

Operating System: Red Hat Linux 8.0
File System: ext2
Other Software: Intel 4.4.19 driver

HTTP Software

Vendor: Red Hat
HTTP Software: Red Hat Content Accelerator 2
API: RHCA user API
Server Cache: None
Log Mode: Binary CLF

Test Sponsor

Test Date: Mar-2003
Tested By: Hewlett-Packard Company
SPEC License: 3

Network

of Controllers: 4
Network Controllers: Integrated NC7781 1000TX, 3 Intel Pro/1000 MT Server Adapters
of Nets: 4
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 16
Model: Compaq Proliant DL380
Processor: 1.0GHz Intel Pentium III
of Processors: 2
Memory: 128MB
Network Controller: Alteon ACENIC 1000SX
Operating System: Red Hat 7.3
Compiler: gcc 2.96

Notes/Tuning Information

SUT Notes

1 disk for OS and logs
5 disks (1 HW RAID0 logical) for fileset

Operating System Notes

Tuning parameters:
ulimit -n 10000, set number of open files to 10000, default 1024
net.core.optmem_max=10000000, maximum amount of option memory buffers, default 10240
net.core.rmem_default=131071, default receive socket buffer size, default 65535
net.core.rmem_max=131071, maximum receive socket buffer size, default 131071
net.core.wmem_default=10000000, default send socket buffer size, default 65535
net.core.wmem_max=10000000, maximum send socket buffer size, default 131071
net.core.hot_list_length=300000, maximum number of skb-heads to be cached, default 128
net.core.netdev_max_backlog=300000, number of unprocessed input packets before kernel starts dropping them, default 300
net.ipv4.tcp_max_tw_buckets=2000000, set TCP time-wait buckets pool size, default 180000
net.ipv4.tcp_rmem=10000000 10000000 10000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
net.ipv4.tcp_wmem=10000000 10000000 10000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072
net.ipv4.tcp_mem=10000000 10000000 10000000, maximum TCP buffer space allocatable, default 195584 196096 196608
net.ipv4.tcp_timestamps=0, turns TCP timestamp support off, default on
net.ipv4.ip_nonlocal_bind=1, allows processes to bind to non-local IP addresses
net.ipv4.tcp_sack=0, turn SACK support off, default on
net.ipv4.tcp_window_scaling=0, turn TCP window scaling support off, default on
File systems mounted with "noatime,nodiratime", no inode access time updating
One NIC bound per logical CPU (Hyper-Threading enabled)

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTP Software Notes

net.tux.cgiroot=/, cgi root check; default /var/www/tux/cgiroot/
net.tux.cgi_uid=99, userid for cgi scripts; default -1
net.tux.cgi_gid=99, groupid for cgi scripts; default -1
net.tux.mode_allowed=255, allowed file permission bits, default 4
net.tux.mode_forbidden=2, forbidden file permission bits, default 0
net.tux.documentroot=/web, document root for web server, default /var/www/tux
net.tux.logging=1, enable logging, default off
net.tux.threads=4, sets number of TUX threads, default 2
net.tux.max_backlog=3000,maximum per-listening-socket TCP backlog size, default 2048
net.tux.noid=1, suppress the Server id string, default 0
net.tux.generate_etags=0, don't generate ETag header, default 1
net.tux.generate_last_mod=0, don't generate Last-Modified header, default 0

HTTP API Notes

Compiled with gcc 3.2 20020903 (Red Hat Linux 8.0 3.2-7)
-fomit-frame-pointer -mcpu=i686 -march=i686 -O2 -Wall -fPIC
-fomit-frame-pointer -mcpu=i686 -march=i686 -O2 -Wall -shared
Flag descriptions in HP-20030317-APIFlags.txt

Network Notes

txqueuelen=20000, transmit queue length, default 100
One Network bound to each TUX thread

Client Notes

net.ipv4.ip_local_port_range = 1024 65535

Other Notes

Tuning Disclosure: See Above
Dynamic API: HP-20030303-RHCA.tar.gz
Kernel config: HP-20030317-DL380G3-config.txt