SPEC ACCEL™ OMP Result

Lenovo

(Test Sponsor: Indiana University)

Intel Xeon E5-2680 v3
Lenovo NeXtScale nx360 M5

SPECaccel_omp_peak = Not Run

SPECaccel_omp_base = 2.32

ACCEL license:	3440A	**Test date:**	Aug-2017
Test sponsor:	Indiana University	**Hardware Availability:**	Sep-2014
Tested by:	Indiana University	**Software Availability:**	Mar-2017



Hardware

CPU Name:	Intel Xeon E5-2680 v3
CPU Characteristics:	Intel Turbo Boost Technology on, Hyper-threading off.
CPU MHz:	2500
CPU MHz Maximum:	3300
FPU:	Integrated
CPU(s) enabled:	24 cores, 2 chips, 12 cores/chip
CPU(s) orderable:	1-2 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	30 MB I+D on chip per chip

Continued on next page

Accelerator

Accel Model Name:	Intel Xeon E5-2680 v3
Accel Vendor:	Intel
Accel Name:	Intel Xeon E5-2680 v3
Type of Accel:	CPU
Accel Connection:	N/A
Does Accel Use ECC:	yes
Accel Description:	Intel Xeon E5-2680 v3 @2.5~3.3GHz
Accel Driver:	None

SPEC ACCEL OMP Result

Lenovo
(Test Sponsor: Indiana University)
Intel Xeon E5-2680 v3
Lenovo NeXtScale nx360 M5

SPECaccel_omp_peak = Not Run

SPECaccel_omp_base = 2.32

ACCEL license: 3440A
Test sponsor: Indiana University
Tested by: Indiana University
Test date: Aug-2017
Hardware Availability: Sep-2014
Software Availability: Mar-2017

Hardware (Continued)

Other Cache: None
Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2133P-R)
Disk Subsystem: None
Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server release 7.3 (Maipo) 3.10.0-514.26.1.el7.x86_64
Compiler: Intel Parallel Studio XE 2017 for Linux Version 17.0.3.191 Build 20170404
File System: Lustre 2.5 (DDN SFA12K) over 10Gb ethernet
System State: Run level 3 (multi-user)
Other Software: None

Results Table

	Base						Peak					
Benchmark	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.postencil	143	0.761	**107**	**1.02**	95.6	1.14						
504.polbm	91.5	1.33	83.2	1.47	**83.2**	**1.47**						
514.pomriq	**509**	**1.22**	510	1.22	508	1.22						
550.pmd	**215**	**1.12**	214	1.12	215	1.12						
551.ppalm	**184**	**2.95**	184	2.95	183	2.97						
552.pep	219	1.05	**215**	**1.07**	215	1.07						
553.pclvrleaf	**339**	**3.38**	341	3.36	322	3.56						
554.pcg	86.4	3.86	**87.0**	**3.83**	87.4	3.81						
555.pseismic	**190**	**1.49**	184	1.53	196	1.44						
556.psp	**110**	**7.47**	110	7.46	98.6	8.29						
557.pcsp	124	6.94	113	7.59	**116**	**7.39**						
559.pmniGhost	183	2.17	192	2.07	**187**	**2.12**						
560.pilbdc	550	1.19	545	1.20	**548**	**1.19**						
563.pswim	**107**	**1.49**	99.0	1.61	109	1.46						
570.pbt	**67.1**	**11.6**	67.2	11.6	66.4	11.8						

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Sysinfo program
/N/dc2/projects/hpc/lijunj/SPEC/accel-1.2-run/carbonate/Docs/sysinfo
$Rev: 6965 $ $Date:: 2015-04-21 #$ c05a7f14b1b1765e3fe1df68447e8a35
running on c13 Thu Aug 10 22:19:47 2017
```

Continued on next page

Platform Notes (Continued)

```
This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/accel/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2680 v3 @ 2.50GHz
      2 "physical id"s (chips)
      24 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 12
      siblings  : 12
      physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13
      physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13
   cache size : 30720 KB

From /proc/meminfo
   MemTotal:       263439912 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   os-release:
      NAME="Red Hat Enterprise Linux Server"
      VERSION="7.3 (Maipo)"
      ID="rhel"
      ID_LIKE="fedora"
      VERSION_ID="7.3"
      PRETTY_NAME="Red Hat Enterprise Linux Server 7.3 (Maipo)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:redhat:enterprise_linux:7.3:GA:server"
   redhat-release: Red Hat Enterprise Linux Server release 7.3 (Maipo)
   system-release: Red Hat Enterprise Linux Server release 7.3 (Maipo)
   system-release-cpe: cpe:/o:redhat:enterprise_linux:7.3:ga:server

uname -a:
   Linux c13 3.10.0-514.26.1.el7.x86_64 #1 SMP Tue Jun 20 01:16:02 EDT 2017
   x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Aug 1 19:29

SPEC is set to: /N/dc2/projects/hpc/lijunj/SPEC/accel-1.2-run/carbonate
   Filesystem                              Type     Size  Used Avail Use% Mounted
   on
   10.10.0.171@o2ib:10.10.0.172@o2ib:/dc2 lustre  5.3P  5.0P  239T  96% /N/dc2
Additional information from dmidecode:
```

Continued on next page

Platform Notes (Continued)

```
    Warning: Use caution when you interpret this section. The 'dmidecode' program
    reads system data which is "intended to allow hardware to be accurately
    determined", but the intent may not be met, as there are frequent changes to
    hardware, firmware, and the "DMTF SMBIOS" standard.


 (End of data from sysinfo program)
```

Base Compiler Invocation

C benchmarks:
`icc`

Fortran benchmarks:
`ifort`

Benchmarks using both Fortran and C:
`icc ifort`

Base Portability Flags

503.postencil: `-DSPEC_USE_INNER_SIMD`
504.polbm: `-DSPEC_USE_INNER_SIMD`
514.pomriq: `-DSPEC_USE_INNER_SIMD`
550.pmd: `-DSPEC_USE_INNER_SIMD -80`
551.ppalm: `-DSPEC_USE_INNER_SIMD`
552.pep: `-DSPEC_USE_INNER_SIMD`
553.pclvrleaf: `-DSPEC_USE_INNER_SIMD`
554.pcg: `-DSPEC_USE_INNER_SIMD`
555.pseismic: `-DSPEC_USE_INNER_SIMD`
556.psp: `-DSPEC_USE_INNER_SIMD`
557.pcsp: `-DSPEC_USE_INNER_SIMD`
559.pmniGhost: `-DSPEC_USE_INNER_SIMD -nofor-main`
560.pilbdc: `-DSPEC_USE_INNER_SIMD`
563.pswim: `-DSPEC_USE_INNER_SIMD`
570.pbt: `-DSPEC_USE_INNER_SIMD`

Base Optimization Flags

C benchmarks:
`-O3 -qopenmp -qopenmp-offload=host -xHost`

Continued on next page

Base Optimization Flags (Continued)

Fortran benchmarks:
`-O3 -qopenmp -qopenmp-offload=host -xHost`

Benchmarks using both Fortran and C:
`-O3 -qopenmp -qopenmp-offload=host -xHost`

The flags file that was used to format this result can be browsed at
https://www.spec.org/accel/flags/Intel-icc17.0-linux64.20170830.html

You can also download the XML flags source by saving the following link:
https://www.spec.org/accel/flags/Intel-icc17.0-linux64.20170830.xml

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC ACCEL v1.2.
Report generated on Wed Aug 30 17:05:11 2017 by SPEC ACCEL PS/PDF formatter v1290.
Originally published on 30 August 2017.