SPEC ACCEL™ OMP Result

Copyright 2015-2023 Standard Performance Evaluation Corporation

Intel
Intel Xeon Platinum 8480+

Intel Server D50DNP2MFALACB (2 x Intel Xeon Platinum 8480+, 2.0GHz, SMT ON, Turbo OFF)

SPECaccel_omp_peak = 16.0

SPECaccel_omp_base = 14.3

ACCEL license:	13	**Test date:**	Jun-2023
Test sponsor:	Intel	**Hardware Availability:**	Jan-2023
Tested by:	Intel	**Software Availability:**	Apr-2023



Hardware

CPU Name:	Intel Xeon Platinum 8480+
CPU Characteristics:	Simultaneous multithreading (SMT) ON, Turbo OFF
CPU MHz:	2000
CPU MHz Maximum:	3800
FPU:	Integrated
CPU(s) enabled:	112 cores, 2 chips, 56 cores/chip, 2 threads/core
CPU(s) orderable:	1, 2 chips
Primary Cache:	32 KB I + 48 KB D on chip per core
Secondary Cache:	2 MB I+D on chip per core
L3 Cache:	105 MB I+D on chip per chip
Other Cache:	None

Continued on next page

Accelerator

Accel Model Name:	Intel Xeon Platinum 8480+
Accel Vendor:	Intel
Accel Name:	Intel Xeon Platinum 8480+
Type of Accel:	CPU
Accel Connection:	N/A
Does Accel Use ECC:	yes
Accel Description:	Intel Xeon Platinum 8480+ SMT ON, Turbo OFF
Accel Driver:	N/A

SPEC ACCEL OMP Result

Copyright 2015-2023 Standard Performance Evaluation Corporation

Intel
Intel Xeon Platinum 8480+

Intel Server D50DNP2MFALACB (2 x Intel Xeon Platinum 8480+, 2.0GHz, SMT ON, Turbo OFF)

SPECaccel_omp_peak = 16.0

SPECaccel_omp_base = 14.3

ACCEL license: 13
Test sponsor: Intel
Tested by: Intel

Test date: Jun-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Hardware (Continued)

Memory: 512 GB (16 x 32 GB 2Rx8 PC5-4800B)
Disk Subsystem: 1 x 1 TB NVMe U.2 2.5" SSD
Other Hardware: None

Software

Operating System: Rocky Linux 8.7 (Green Obsidian)
Rocky Linux release 8.8 (Green Obsidian)
4.18.0-477.13.1.el8_8.x86_64
Compiler: Intel oneAPI Compiler 2023.1.0
File System: PANASAS FS
System State: Run level 3
Other Software: FFTW 3.3.10

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.postencil	10.3	10.6	**11.2**	**9.76**	11.3	9.64	10.3	10.6	**11.2**	**9.76**	11.3	9.64
504.polbm	7.55	16.2	8.80	13.9	**8.28**	**14.7**	7.55	16.2	8.80	13.9	**8.28**	**14.7**
514.pomriq	47.4	13.1	50.1	12.4	**48.9**	**12.7**	47.4	13.1	50.1	12.4	**48.9**	**12.7**
550.pmd	**12.8**	**18.8**	12.8	18.8	12.9	18.7	12.2	19.7	11.9	20.2	**12.1**	**20.0**
551.ppalm	150	3.63	149	3.65	**150**	**3.64**	47.9	11.4	**45.5**	**11.9**	45.4	12.0
552.pep	**27.1**	**8.52**	27.4	8.42	27.0	8.57	**27.1**	**8.52**	27.4	8.42	27.0	8.57
553.pclvrleaf	**53.5**	**21.4**	53.1	21.5	55.5	20.6	51.4	22.3	50.2	22.8	**50.9**	**22.5**
554.pcg	**33.3**	**10.0**	32.3	10.3	33.6	9.91	33.5	9.94	33.3	10.0	**33.3**	**9.99**
555.pseismic	37.5	7.53	**41.9**	**6.73**	43.3	6.51	37.5	7.53	**41.9**	**6.73**	43.3	6.51
556.psp	19.2	42.6	**19.1**	**42.9**	17.4	47.1	19.2	42.6	**19.1**	**42.9**	17.4	47.1
557.pcsp	**20.2**	**42.6**	21.8	39.3	19.7	43.6	**20.2**	**42.6**	21.8	39.3	19.7	43.6
559.pmniGhost	53.8	7.38	54.4	7.30	**54.0**	**7.35**	48.7	8.16	**48.7**	**8.16**	48.6	8.17
560.pilbdc	**61.5**	**10.6**	60.9	10.7	61.7	10.6	**55.1**	**11.9**	55.4	11.8	55.0	11.9
563.pswim	**8.03**	**19.8**	7.89	20.1	8.03	19.8	**8.03**	**19.8**	7.89	20.1	8.03	19.8
570.pbt	**15.9**	**49.0**	15.1	51.7	16.1	48.5	13.8	56.5	13.7	57.0	**13.8**	**56.7**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
```

Platform Notes

```
Sysinfo program
/global/panfs02/innl/abobyr/SpecACCEL_OMP/kits/kit1.4_submission/Docs/sysinfo
$Rev: 6965 $ $Date:: 2015-04-21 #$ c05a7f14b1b1765e3fe1df68447e8a35
running on eedq017 Thu Jun 29 14:29:02 2023

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/accel/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel Xeon Platinum 8480+
      2 "physical id"s (chips)
      224 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 56
      siblings  : 112
      physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
      22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46
      47 48 49 50 51 52 53 54 55
      physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
      22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46
      47 48 49 50 51 52 53 54 55
   cache size : 107520 KB

From /proc/meminfo
   MemTotal:       528079220 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   centos-release: Rocky Linux release 8.8 (Green Obsidian)
   os-release:
      NAME="Rocky Linux"
      VERSION="8.8 (Green Obsidian)"
      ID="rocky"
      ID_LIKE="rhel centos fedora"
      VERSION_ID="8.8"
      PLATFORM_ID="platform:el8"
      PRETTY_NAME="Rocky Linux 8.8 (Green Obsidian)"
      ANSI_COLOR="0;32"
   redhat-release: Rocky Linux release 8.8 (Green Obsidian)
   rocky-release: Rocky Linux release 8.8 (Green Obsidian)
   rocky-release-upstream: Derived from Red Hat Enterprise Linux 8.8
   system-release: Rocky Linux release 8.8 (Green Obsidian)
   system-release-cpe: cpe:/o:rocky:rocky:8:GA

uname -a:
```

Continued on next page

Platform Notes (Continued)

```
      Linux eedq017 4.18.0-477.13.1.el8_8.x86_64 #1 SMP Tue May 30 22:15:39 UTC
      2023 x86_64 x86_64 x86_64 GNU/Linux

   run-level 3 Jun 29 14:23

   SPEC is set to: /global/panfs02/innl/abobyr/SpecACCEL_OMP/kits/kit1.4_submission
      Filesystem                Type   Size  Used Avail Use% Mounted on
      panfs://36.101.212.1/innl panfs  269T  245T   25T  91% /global/panfs02/innl
   Additional information from dmidecode:

      Warning: Use caution when you interpret this section. The 'dmidecode' program
      reads system data which is "intended to allow hardware to be accurately
      determined", but the intent may not be met, as there are frequent changes to
      hardware, firmware, and the "DMTF SMBIOS" standard.


   (End of data from sysinfo program)
```

General Notes

```
The PANASAS filesystem as described on this result page was formerly
generally available.  At the time of this publication, it may
not be shipping, and/or may not be supported, and/or may fail
to meet other tests of General Availability described in the
SPEC HPG Policy document, http://www.spec.org/hpg/policy.html
```

Base Compiler Invocation

C benchmarks:
icc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

503.postencil: -DSPEC_USE_INNER_SIMD
504.polbm: -DSPEC_USE_INNER_SIMD
514.pomriq: -DSPEC_USE_INNER_SIMD
550.pmd: -DSPEC_USE_INNER_SIMD -80

Continued on next page

Base Portability Flags (Continued)

551.ppalm: -DSPEC_USE_INNER_SIMD
552.pep: -DSPEC_USE_INNER_SIMD
553.pclvrleaf: -DSPEC_USE_INNER_SIMD
554.pcg: -DSPEC_USE_INNER_SIMD
555.pseismic: -DSPEC_USE_INNER_SIMD
556.psp: -DSPEC_USE_INNER_SIMD
557.pcsp: -DSPEC_USE_INNER_SIMD
559.pmniGhost: -DSPEC_USE_INNER_SIMD -nofor-main
560.pilbdc: -DSPEC_USE_INNER_SIMD
563.pswim: -DSPEC_USE_INNER_SIMD
570.pbt: -DSPEC_USE_INNER_SIMD

Base Optimization Flags

C benchmarks:
-Ofast -xCORE-AVX512 -qopt-zmm-usage=high -no-prec-sqrt -qopenmp
-qopenmp-offload=host -ipo -ansi-alias
-qopt-multiple-gather-scatter-by-shuffles
-fimf-precision=low:exp,sin,cos,sincos,log

Fortran benchmarks:
-Ofast -xCORE-AVX512 -qopt-zmm-usage=high -no-prec-sqrt -qopenmp
-qopenmp-offload=host -ipo -ansi-alias
-qopt-multiple-gather-scatter-by-shuffles
-fimf-precision=low:exp,sin,cos,sincos,log

Benchmarks using both Fortran and C:
-Ofast -xCORE-AVX512 -qopt-zmm-usage=high -no-prec-sqrt -qopenmp
-qopenmp-offload=host -ipo -ansi-alias
-qopt-multiple-gather-scatter-by-shuffles
-fimf-precision=low:exp,sin,cos,sincos,log

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

570.pbt: icx

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

503.postencil: -DSPEC_USE_INNER_SIMD
504.polbm: -DSPEC_USE_INNER_SIMD
514.pomriq: -DSPEC_USE_INNER_SIMD
550.pmd: -DSPEC_USE_INNER_SIMD -80
551.ppalm: -DSPEC_USE_INNER_SIMD -DSPEC_HOST_FFTW3
552.pep: -DSPEC_USE_INNER_SIMD
553.pclvrleaf: -DSPEC_USE_INNER_SIMD
554.pcg: -DSPEC_USE_INNER_SIMD
555.pseismic: -DSPEC_USE_INNER_SIMD
556.psp: -DSPEC_USE_INNER_SIMD
557.pcsp: -DSPEC_USE_INNER_SIMD
559.pmniGhost: -DSPEC_USE_INNER_SIMD -nofor-main
560.pilbdc: -DSPEC_USE_INNER_SIMD
563.pswim: -DSPEC_USE_INNER_SIMD
570.pbt: -DSPEC_USE_INNER_SIMD

Peak Optimization Flags

C benchmarks:

503.postencil: basepeak = yes

504.polbm: basepeak = yes

514.pomriq: basepeak = yes

552.pep: basepeak = yes

554.pcg: -Ofast -xCORE-AVX512 -qopt-zmm-usage=high -no-prec-sqrt
-qopenmp -qopenmp-offload=host -ipo -ansi-alias
-qopt-multiple-gather-scatter-by-shuffles
-fimf-precision=low:exp,sin,cos,sincos,log

557.pcsp: basepeak = yes

570.pbt: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp
-ffast-math -flto -funroll-loops -fimf-precision=low

Fortran benchmarks:

550.pmd: -Ofast -xCORE-AVX512 -qopt-zmm-usage=high -no-prec-sqrt
-qopenmp -qopenmp-offload=host -ipo -ansi-alias
-qopt-multiple-gather-scatter-by-shuffles
-fimf-precision=low:exp,sin,cos,sincos,log
-fimf-precision=low -ip

Continued on next page

Peak Optimization Flags (Continued)

551.ppalm: `-Ofast -xCORE-AVX512 -qopt-zmm-usage=high -no-prec-sqrt -qopenmp -qopenmp-offload=host -ipo -ansi-alias -qopt-multiple-gather-scatter-by-shuffles -fimf-precision=low:exp,sin,cos,sincos,log -I/home/abobyr/FFTW-3.3.10/include -L/home/abobyr/FFTW-3.3.10/lib`

555.pseismic: `basepeak = yes`

556.psp: `basepeak = yes`

560.pilbdc: `-Ofast -xCORE-AVX512 -qopt-zmm-usage=high -no-prec-sqrt -qopenmp -qopenmp-offload=host -ipo -ansi-alias -qopt-multiple-gather-scatter-by-shuffles -fimf-precision=low:exp,sin,cos,sincos,log`

563.pswim: `basepeak = yes`

Benchmarks using both Fortran and C:
`-Ofast -xCORE-AVX512 -qopt-zmm-usage=high -no-prec-sqrt -qopenmp -qopenmp-offload=host -ipo -ansi-alias -qopt-multiple-gather-scatter-by-shuffles -fimf-precision=low:exp,sin,cos,sincos,log`

Peak Other Flags

Fortran benchmarks:

551.ppalm: `-lfftw3`

The flags file that was used to format this result can be browsed at
`https://www.spec.org/accel/flags/Intel-icc2021.2-linux64.20230726.html`

You can also download the XML flags source by saving the following link:
`https://www.spec.org/accel/flags/Intel-icc2021.2-linux64.20230726.xml`

Copyright 2015-2023 Standard Performance Evaluation Corporation

Intel
Intel Xeon Platinum 8480+

Intel Server D50DNP2MFALACB (2 x Intel Xeon Platinum 8480+, 2.0GHz, SMT ON, Turbo OFF)

SPECaccel_omp_peak = 16.0

SPECaccel_omp_base = 14.3

ACCEL license:	13	**Test date:**	Jun-2023
Test sponsor:	Intel	**Hardware Availability:**	Jan-2023
Tested by:	Intel	**Software Availability:**	Apr-2023

SPEC ACCEL is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC ACCEL v1.4.
Report generated on Wed Aug 16 15:10:28 2023 by SPEC ACCEL PS/PDF formatter v1290.
Originally published on 16 August 2023.