CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 1600

SPECint2000 = 311

SPECint_base2000 = 292

SPEC license #: 6 | Tested by: Sun Microsystems, Palo Alto | Test date: Mar-2001 | Hardware Avail: Sep-2000 | Software Avail: Mar-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	602	233	596	235
175.vpr	1400	550	255	516	271
176.gcc	1100	341	323	333	331
181.mcf	1800	571	315	536	336
186.crafty	1000	340	294	312	320
197.parser	1800	672	268	622	289
252.eon	1300	426	305	398	327
253.perlbmk	1800	594	303	569	317
254.gap	1100	507	217	498	221
255.vortex	1900	478	397	405	469
256.bzip2	1500	470	319	440	341
300.twolf	3000	927	324	873	344



Hardware

CPU:	UltraSPARC-III
CPU MHz:	600
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1-2
Parallel:	None
Primary Cache:	32KBI+64KBD on chip
Secondary Cache:	4MB(I+D) off chip
L3 Cache:	None
Other Cache:	None
Memory:	1GB
Disk Subsystem:	1 x 18GB
Other Hardware:	--

Software

Operating System:	Solaris 8 10/00
Compiler:	Forte Developer 6 update 1 w/ latest patches
File System:	UFS
System State:	Single User

Notes/Tuning Information

```
Portability:
    176.gcc:     -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
    186.crafty:  -DSUN
    252.eon:     -library=iostream
    253.perlbmk: -DSPEC_CPU2000_SOLARIS
    254.gap:     -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
                 -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

Base C   flags: -fast -xcrossfile -xprofile
Base C++ flags: -fast -xcrossfile -xprofile

Peak:
164.gzip: -fast -xalias_level=std -xcrossfile -W2,-whole -xprofile
175.vpr: -fast -xalias_level=std -xcrossfile -xdepend -xregs=syst -W2,-whole -xprofile
         -lmopt
176.gcc: -fast -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xprofile
181.mcf: -fast -xcrossfile -xdepend -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xsafe=mem
         -xprofile
186.crafty: -fast -xcrossfile -Wc,-Qgsched-trace_late=1,-Qgsched-T4
            -xalias_level=strong -xregs=syst -xchip=ultra2 -xprofile
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
197.parser: -fast -xcrossfile -xdepend -xregs=syst -Wc,-Qgsched-trace_late=1,-Qgsched-T4
            -xalias_level=strong -xprofile
252.eon: -fast -xcrossfile -xsafe=mem -Qoption iropt -Mt500,-restrict_g,-restrict
         -Qoption cg -Qgsched-trace_late=1,-Qgsched-T4 -xprofile
253.perlbmk: -fast -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qgsched-trace_spec_load=1
             -xcrossfile -xalias_level=std -xsafe=mem -xprofile
254.gap: -fast -xarch=v8 -W2,-crit,-whole -xcrossfile -Wc,-Qiselect-funcalign=32
         -xalias_level=std -xprofile
255.vortex: -fast -xsafe=mem -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Ms1,-Mt500,-Mr6000,-crit
            -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32 -Wc,-Qpeep-Sh0
            -xrestrict -xdepend -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xprofile
256.bzip2: -fast -xarch=v8 -W2,-Abopt -xcrossfile -xalias_level=strong
           -Wc,-Qiselect-funcalign=32 -xdepend -xregs=syst -xprofile
300.twolf: -fast -xalias_level=strong -W2,-whole -xsafe=mem -xprofile

Note: ONESTEP=yes for all benchmarks.

Forte Developer 6 update 1 patches include:
   109503-02,109504-01,109505-08,109506-02,109508-04,109510-01,109513-06

Patch 111228-01 and obp 4.0.40 (or later) is required.

System configuration details located (as of June 2001) at
        http://www.sun.com/desktop/sunblade1000
```