



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer GS80 68/1224

SPECint_rate2000 = NC
SPECint_rate_base2000 = NC

SPEC license #: 2

Tested by: HPQ - NH

Test date:

Jul-2002 Hardware Avail:

Aug-2002 Software Avail:

Nov-2001

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

5	4	3	2	1		Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
						164.gzip	8	NC	NC	8	NC	NC
						175.vpr	8	NC	NC	8	NC	NC
						176.gcc	8	NC	NC	8	NC	NC
						181.mcf	8	NC	NC	8	NC	NC
						186.crafty	8	NC	NC	8	NC	NC
						197.parser	8	NC	NC	8	NC	NC
						252.eon	8	NC	NC	8	NC	NC
						253.perlbench	8	NC	NC	8	NC	NC
						254.gap	8	NC	NC	8	NC	NC
						255.vortex	8	NC	NC	8	NC	NC
						256.bzip2	8	NC	NC	8	NC	NC
						300.twolf	8	NC	NC	8	NC	NC

Hardware		Software	
CPU:	Alpha 21264C	Operating System:	Tru64 UNIX V5.1B
CPU MHz:	1224	Compiler:	Compaq C V6.4-215-46B7O
FPU:	Integrated		Program Analysis Tools V2.0
CPU(s) enabled:	8 cores, 8 chips, 1 core/chip		Spike V5.2 DTK (1.471.2.2 46B5P)
CPU(s) orderable:	1 to 8		Compaq C++ V6.3-010-46B2F
Parallel:	No	File System:	ufs
Primary Cache:	64KB(I)+64KB(D) on chip	System State:	Multi-user
Secondary Cache:	16MB off chip per CPU		
L3 Cache:	None		
Other Cache:	None		
Memory:	32GB		
Disk Subsystem:	18GB Hard Drive		
Other Hardware:	None		

Notes/Tuning Information

Baseline C : cc -arch ev6 -fast +CFB ONESTEP
C++: cxx -arch ev6 -O2 ONESTEP

Peak:

All but 252.eon: cc -g3 -arch ev6 ONESTEP
164.gzip: -fast -O4 -non_shared +CFB
175.vpr: -fast -O4 -assume restricted_pointers +CFB
176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc -none
+CFB +IFB



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer GS80 68/1224

SPECint_rate2000 = NC
SPECint_rate_base2000 = NC

SPEC license #: 2

Tested by:

HPQ - NH

Test date:

Jul-2002

Hardware Avail:

Aug-2002

Software Avail:

Nov-2001

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

Notes/Tuning Information (Continued)

```
181.mcf: -fast -xtaso_short +CFB +IFB +PFB
186.crafty: same as base
197.parser: -fast -O4 -xtaso_short -non_shared +CFB
  252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -none
253.perlbmk: -fast -non_shared +CFB +IFB
  254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
255.vortex: -fast -non_shared +CFB +IFB
  256.bzip2: -fast -O4 -non_shared +CFB
  300.twolf: -fast -O4
             -ldensemalloc -non_shared +CFB +IFB
```

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```
mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*
```

and these flags are added to the first and second compiles:

```
PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use      -prof_dir /tmp/pp
```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```
mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}
```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer GS80 68/1224

SPECint_rate2000 = NC
SPECint_rate_base2000 = NC

SPEC license #: 2

Tested by:

HPQ - NH

Test date:

Jul-2002

Hardware Avail:

Aug-2002

Software Avail:

Nov-2001

SPEC has determined that this result was not in compliance with the SPEC CPU2000 run and reporting rules. Specifically, the submitter has reported that the 3 month availability requirement in the SPEC CPU2000 run rules will not be met due to a change in availability date for the operating system.

Notes/Tuning Information (Continued)

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA
perlchk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO
-DSPEC_CPU2000_LP64

vm:

```
vm_bigpg_enabled = 1  
vm_bigpg_thresh = 16  
vm_swap_eager = 0
```

proc:

```
max_per_proc_address_space = 0x400000000000  
max_per_proc_data_size = 0x400000000000  
max_per_proc_stack_size = 0x400000000000  
max_proc_per_user = 2048  
max_threads_per_user = 0  
maxusers = 16384  
per_proc_address_space = 0x400000000000  
per_proc_data_size = 0x400000000000  
per_proc_stack_size = 0x400000000000
```

submit = runon <cpu no> \$command

Submitted_by: "Beer, Chris" <Chris.Beer@hp.com>

Submitted: Thu Aug 1 16:15:34 2002

Submission: cpu2000-20020801-01532.sub