CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 630 Model 6C4 (1200 MHz, 4 CPU)

SPECfp_rate2000 = 35.1

SPECfp_rate_base2000 = 34.2

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Mar-2003 | Hardware Avail: Apr-2003 | Software Avail: Feb-2003



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	148	50.1	4	148	50.3
171.swim	4	406	35.4	4	406	35.4
172.mgrid	4	308	27.2	4	283	29.5
173.applu	4	375	26.0	4	374	26.1
177.mesa	4	236	27.5	4	198	32.9
178.galgel	4	146	92.1	4	136	98.8
179.art	4	332	36.3	4	354	34.1
183.equake	4	170	35.4	4	170	35.4
187.facerec	4	204	43.2	4	203	43.4
188.ammp	4	396	25.8	4	396	25.8
189.lucas	4	285	32.6	4	281	33.0
191.fma3d	4	355	27.5	4	343	28.4
200.sixtrack	4	216	23.6	4	212	24.1
301.apsi	4	384	31.4	4	379	31.8

Hardware

CPU:	POWER4+
CPU MHz:	1200
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip, 1 chip/SCM
CPU(s) orderable:	1,2,4 (order by # cores)
Parallel:	No
Primary Cache:	64KBI+32KBD (on chip) per core
Secondary Cache:	1536KB unified (on chip) per chip
L3 Cache:	8MB unified (off-chip) per SCM, 2 SCMs in SUT
Other Cache:	None
Memory:	16 GB
Disk Subsystem:	1x36GB SCSI
Other Hardware:	None

Software

Operating System:	AIX 5L V5.2 PTF 2
Compiler:	IBM C for AIX, Version 6.0 IBM XL FORTRAN for AIX, Version 8.1.0.3 Other Software: ESSL 3.3, MASS 3.0
File System:	AIX/JFS
System State:	Multi-User

Notes/Tuning Information

```
Portability Flags
  -qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu, 178.galgel,
   200.sixtrack, 301.apsi
  -qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

Base Optimization Flags:
  C:
  -O5 -qalign=natural -blpdata -lmass
  Fortran:
  -O5 -qalign=natural -blpdata -lmass

Floating Point Peak Flags
168.wupwise
  -O5 -qipa=partition=large
171.swim
  -O4 -q64 -blpdata
172.mgrid
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    -O5 -qarch=pwr3 -qtune=pwr3 -blpdata
  173.applu
    -O3 -qarch=pwr3 -qtune=pwr3 -lmass -qhot -blpdata
  177.mesa
    -qpdf1/pdf2
    fdpr -v -R3
    -O3 -qarch=pwr3 -qtune=pwr3 -qipa=level=2 -qalign=natural -blpdata
  178.galgel
    -qpdf1/pdf2
    fdpr -v -R3
    -O5 -qalign=natural -qessl -lessl -lmass -blpdata
  179.art
   -O4 -lhmu
  183.equake
    BASEPEAK = 1
  187.facerec
    fdpr -v -R3
    -O5 -lmass -blpdata
  188.ammp
    BASEPEAK = 1
  189.lucas
    -O3 -q64 -blpdata
  191.fma3d
    -qpdf1/pdf2
    -O5 -qarch=pwr4 -qtune=pwr3 -lhmu -qalign=natural -blpdata
  200.sixtrack
    -qpdf1/pdf2
    -O5 -lmass
  301.apsi
    -O5 -qarch=pwr4 -qtune=pwr3 -blpdata

    SCM: Acronym for "Single-Chip Module"
    SUT: Acronym for "System Under Test"

    fpdr: Feedback directed program restructuring tool
    /usr/spec2000 filesystem mounted with no JFS log file I/O.
    APAR IY 38292 was applied to AIX to enable new hardware support.
    ulimits set to unlimited.
    C: IBM VAC++ invoked as xlc
    Fortran 77 and 90: IBM XL Fortran for AIX invoked as xlf90.
    Large page mode and memory affinity were set as follows:
    vmo -r -o lgpg_regions=128 -o lgpg_size=16777216 -o memory_affinity=1
      chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
      shutdown -r
      export MEMORY_AFFINITY=MCM
```