



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G3(3.2GHz/1MB L3 cache, Intel Xeon)

SPECint_rate2000 = 28.0
SPECint_rate_base2000 = 26.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Sep-2003 Hardware Avail: Oct-2003 Software Avail: Sep-2003

										Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
45	40	35	30	25	20	15	10	5		164.gzip	2	113	28.8	2	113	28.8
										175.vpr	2	184	17.7	2	179	18.1
										176.gcc	2	79.6	32.1	2	68.9	37.0
										181.mcf	2	375	11.1	2	367	11.4
										186.crafty	2	82.2	28.2	2	82.5	28.1
										197.parser	2	157	26.6	2	157	26.6
										252.eon	2	92.3	32.7	2	78.8	38.3
										253.perlbnk	2	130	32.2	2	120	34.9
										254.gap	2	77.4	33.0	2	77.4	33.0
										255.vortex	2	105	41.9	2	105	41.9
										256.bzip2	2	176	19.8	2	169	20.6
										300.twolf	2	269	25.8	2	189	36.7

Hardware

CPU: Intel Xeon (3.2GHz, 533MHz bus)
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading disabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12K micro-ops I + 8KBD on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: 1024KB(I+D) on chip
 Other Cache: N/A
 Memory: 4x512MB PC2100
 Disk Subsystem: 2x36.4GB 15K Ultra320 SCSI
 Other Hardware:

Software

Operating System: Windows 2000 Server(Build 2195 SP3)
 Compiler: Intel C++ Compiler 7.1 Build 20030813Z
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Hyper Threading disabled in BIOS

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -QxW -Qipo -O3 +FDO ONESTEP=yes
Base tuning for C++ programs: -Qipo -GX -GR +FDO ONESTEP=yes
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -O3 -QxW -Qipo +FDO ONESTEP=yes
175.vpr: -QxW -Qipo -O3 +FDO ONESTEP=yes
176.gcc: -QxW -Qipo -Oi- -O3 +FDO ONESTEP=yes
181.mcf: -Oa -Qipo +FDO shlw32M.lib ONESTEP=yes
186.crafty: -QxW -Qipo -O3 +FDO ONESTEP=yes
197.parser: -QxW -Qipo -Oa -O3 +FDO ONESTEP=yes
252.eon: -QxW -Qipo -O3 +FDO shlw32M.lib ONESTEP=yes
253.perlbnk: -Qipo -Oa -O3 +FDO shlw32M.lib ONESTEP=yes
254.gap: -QxW -Qipo -O3 +FDO ONESTEP=yes
255.vortex: -QxW -Qipo -O3 +FDO ONESTEP=yes
256.bzip2: -Qunroll1 -Oa -Qipo +FDO ONESTEP=yes
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G3(3.2GHz/1MB L3 cache, Intel Xeon)

SPECint_rate2000 = 28.0
SPECint_rate_base2000 = 26.1

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Sep-2003 | Hardware Avail: Oct-2003 | Software Avail: Sep-2003

Notes/Tuning Information (Continued)

300.twolf: -QxW -Qipo -O3 -Oa +FDO shlw32M.lib ONESTEP=yes