



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL140(3.2GHz/1MB L3 cache, Intel Xeon)

SPECint_rate2000 = 26.1
SPECint_rate_base2000 = 24.4

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Nov-2003 Hardware Avail: Nov-2003 Software Avail: Nov-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	115	28.4	2	114	28.4
175.vpr	2	193	16.8	2	193	16.8
176.gcc	2	92.0	27.8	2	75.3	33.9
181.mcf	2	496	8.42	2	501	8.33
186.crafty	2	82.1	28.3	2	82.0	28.3
197.parser	2	166	25.1	2	166	25.2
252.eon	2	91.9	32.8	2	78.4	38.5
253.perlbnk	2	131	32.0	2	120	34.9
254.gap	2	87.5	29.2	2	87.6	29.1
255.vortex	2	112	39.4	2	112	39.5
256.bzip2	2	191	18.2	2	188	18.6
300.twolf	2	274	25.4	2	189	36.8

Hardware

CPU: Intel Xeon (3.2GHz, 533MHz bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 1024KB(I+D) on chip
Other Cache: N/A
Memory: 4x512MB PC2100
Disk Subsystem: 1x80GB ATA/100 7200 rpm
Other Hardware:

Software

Operating System: Windows 2000 Server(Build 2195 SP3)
Compiler: Intel C++ Compiler 7.1 Build 20030813Z
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -QxW -Qipo -O3 +FDO ONESTEP=yes
Base tuning for C++ programs: -Qipo -GX -GR +FDO ONESTEP=yes
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -O3 -QxW -Qipo +FDO ONESTEP=yes
175.vpr: -QxW -Qipo -O3 +FDO ONESTEP=yes
176.gcc: -QxW -Qipo -Oi- -O3 +FDO ONESTEP=yes
181.mcf: -Oa -Qipo +FDO shlw32M.lib ONESTEP=yes
186.crafty: -QxW -Qipo -O3 +FDO ONESTEP=yes
197.parser: -QxW -Qipo -Oa -O3 +FDO ONESTEP=yes
252.eon: -QxW -Qipo -O3 +FDO ONESTEP=yes
253.perlbnk: -Qipo -Oa -O3 +FDO shlw32M.lib ONESTEP=yes
254.gap: -QxW -Qipo -O3 +FDO ONESTEP=yes
255.vortex: -QxW -Qipo -O3 +FDO ONESTEP=yes
256.bzip2: -Qunroll1 -Oa -Qipo +FDO ONESTEP=yes
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL140(3.2GHz/1MB L3 cache, Intel Xeon)

SPECint_rate2000 = 26.1
SPECint_rate_base2000 = 24.4

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Nov-2003 | Hardware Avail: Nov-2003 | Software Avail: Nov-2003

Notes/Tuning Information (Continued)

300.twolf: -QxW -Qipo -O3 -Oa +FDO shlw32M.lib ONESTEP=yes
BIOS Configuration Notes
Hyper Threading disabled