CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP 9000 rp3440-4 (1000MHz PA-8800)

SPECint_rate2000 = 18.7

SPECint_rate_base2000 = 17.9

SPEC license #: 3 | Tested by: HP Richardson | Test date: Jan-2004 | Hardware Avail: Feb-2004 | Software Avail: Feb-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	204	15.9	2	201	16.2
175.vpr	2	186	17.5	2	186	17.5
176.gcc	2	108	23.7	2	108	23.7
181.mcf	2	297	14.0	2	297	14.0
186.crafty	2	109	21.2	2	109	21.2
197.parser	2	291	14.4	2	278	15.0
252.eon	2	178	16.9	2	157	19.2
253.perlbmk	2	225	18.6	2	192	21.7
254.gap	2	235	10.8	2	231	11.0
255.vortex	2	123	35.8	2	116	38.0
256.bzip2	2	227	15.3	2	203	17.2
300.twolf	2	343	20.3	2	338	20.6

Hardware

CPU:	PA-8800
CPU MHz:	1000
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	2,4 (order by # cores)
Parallel:	no
Primary Cache:	0.75MBI + 0.75MBD (on chip) per core
Secondary Cache:	32MB (off chip) shared by 2 cores
L3 Cache:	N/A
Other Cache:	N/A
Memory:	6GB (12 * 512MB DIMMs)
Disk Subsystem:	1x73GB 15K rpm SCSI
Other Hardware:	N/A

Software

Operating System:	HPUX11i-TCOE B.11.11.0312
Compiler:	HP C/ANSI C B.11.11.08 HP aC++ Compiler A.03.52
File System:	VxFS
System State:	Multi-user

Notes/Tuning Information

```
Portability flags:
  176.gcc: -DHOST_WORDS_BIG_ENDIAN
  186.crafty: -DHP
  252.eon: -DFMAX_IS_DOUBLE
  253.perlbmk: -DSPEC_CPU2000_HP
  254.gap: -DSPEC_CPU2000_HP -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO
           -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

Baseline compile flags:
  C      : +I/+P +Oall +Ostatic_prediction -Wl,-a,archive
  C++    : +I/+P +Oall +Ostatic_prediction -Wl,-a,archive

Peak compile flags:
     164.gzip: +I/+P +Oall +Optrs_strongly_typed +Oinline_budget=800
               -Wl,-a,archive +Ostatic_prediction
      175.vpr: basepeak=true
      176.gcc: basepeak=true
      181.mcf: basepeak=true
   186.crafty: basepeak=true
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    197.parser: +I/+P +Oall +Odataprefetch +ESfic +Oinline_budget=400
                +Owhole_program_mode -Wl,-a,archive +Ostatic_prediction
       252.eon: +I/+P +noeh +O4 +Optrs_strongly_typed +Olibcalls +Oentrysched
                +A +ESfic -Wl,-a,archive +Ostatic_prediction
  253.perlbmk: +I/+P +Oall +ESlit +ESfic +Optrs_strongly_typed
                +Opromote_indirect_calls -Wl,-a,archive +Ostatic_prediction
                linked with /opt/langtools/lib/fastmem.o
       254.gap: +I/+P +Oall +ESlit +ESfic +Optrs_strongly_typed
                +Opromote_indirect_calls -Wl,-a,archive +Ostatic_prediction
    255.vortex: +I/+P +Oall +Oinline_budget=800 +Optrs_strongly_typed
                -Wl,-a,archive +Ostatic_prediction
     256.bzip2: +I/+P +Oall +Odataprefetch +Optrs_strongly_typed +Owhole_program_mode
               +Onoptrs_to_globals +Oinline_budget=80 -Wl,-a,archive +Ostatic_prediction
    300.twolf: +I/+P +Oall +Optrs_strongly_typed -Wl,-a,archive +Ostatic_prediction

Kernel Tunables:
  dbc_max_pct=20
  dbc_min_pct=20
  maxssiz=401604608
  vps_pagesize=4096
  vps_ceiling=16384

Other notes:

  The system under test had the HP-UX 11i v1 December 2003
  Technical Computing Operating Environment (version 11.11.0312)
  and DART63 (December 2003) compilers installed, with the
  following patches applied:

  GOLDAPPS11i Gold Applications Patches for HP-UX 11i v1, December 2003
  GOLDBASE11i Gold Base Patches for HP-UX 11i v1, December 2003
  HWEnable11i Hardware Enablement Patches for HP-UX 11i v1, December 2003
  HWETEST1111 Hardware Enablement Patches for PA-8800 (prerelease)
  PHSS_29483  aC++ compiler cumulative patch (A.03.52)
  PHSS_30002  Fortran90 cumulative patch (B.11.01.74)

   BCH shell utility command 'co cpu' (configure cpu)
      used to deconfigure processors if necessary.
```