CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Altix 350 (1400MHz/3MB, Itanium 2)

SPECint_rate2000 = --

SPECint_rate_base2000 = 49.2

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2004 | Hardware Avail: May-2004 | Software Avail: Jun-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	162	40.2			
175.vpr	4	161	40.5			
176.gcc	4	93.0	54.9			
181.mcf	4	174	48.0			
186.crafty	4	91.5	50.7			
197.parser	4	224	37.3			
252.eon	4	92.1	65.5			
253.perlbmk	4	174	48.1			
254.gap	4	141	36.1			
255.vortex	4	111	79.7			
256.bzip2	4	148	46.9			
300.twolf	4	237	58.7			

Hardware

CPU:	Intel Itanium 2
CPU MHz:	1400
FPU:	Integrated
CPU(s) enabled:	4 cores, 4 chips, 1 core/chip
CPU(s) orderable:	2-16
Parallel:	No
Primary Cache:	16KBI + 16KBD (on chip) per core
Secondary Cache:	256KB (on chip) per core
L3 Cache:	3.0MB (on chip) per core
Other Cache:	N/A
Memory:	16 GB (16*512MB PC2100 DIMMS per 2core module)
Disk Subsystem:	1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
Other Hardware:	None

Software

Operating System:	SGI ProPack(TM) v3.0
Compiler:	Intel(R) C++ Compiler for Linux 8.0 (Build 20040318) MicroQuill SmartHeap Library 7.01 (www.microquill.com)
File System:	xfs
System State:	Single-user

Notes/Tuning Information

```
+FDO: PASS1=-prof_gen  PASS2=-prof_use

Baseline optimization flags:
  C programs:       -fast -auto_ilp32 +FDO
  C++ programs:     -fast -ansi_alias +FDO
  Extra Libraries:  libsmartheap64.a

Portability Flags:
  176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca
  186.crafty: -DLINUX_i386
  252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST -DFMAX_IS_DOUBLE
  253.perlbmk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
               -DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
  254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
           -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
  255.vortex: -DSPEC_CPU2000_LP64 srcalt=closed_files

Processes were bound to CPUs using dplace.
```