CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION Computer Systems

BX41 (3GHz Xeon MP processor w. 4MB L3 cache)

SPECint_rate2000 = 60.0

SPECint_rate_base2000 = 60.0

SPEC license #: 2697 | Tested by: ION | Test date: May-2004 | Hardware Avail: May-2004 | Software Avail: Apr-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	124	52.3	4	124	52.3
175.vpr	4	141	45.9	4	141	45.9
176.gcc	4	78.2	65.2	4	78.2	65.2
181.mcf	4	172	48.6	4	172	48.6
186.crafty	4	88.0	52.7	4	88.0	52.7
197.parser	4	141	59.1	4	141	59.1
252.eon	4	89.3	67.5	4	89.3	67.5
253.perlbmk	4	118	70.7	4	118	70.7
254.gap	4	118	43.3	4	118	43.3
255.vortex	4	84.2	105	4	84.2	105
256.bzip2	4	121	57.6	4	121	57.6
300.twolf	4	189	73.6	4	189	73.8

Hardware

CPU:	Intel Xeon processor, 400MHz system bus
CPU MHz:	2985
FPU:	Integrated
CPU(s) enabled:	4 cores, 4 chips, 1 core/chip, HyperThreading disabled
CPU(s) orderable:	1-4
Parallel:	No
Primary Cache:	12K(I) micro-ops + 8KB(D) on chip
Secondary Cache:	512KB (I+D) on chip
L3 Cache:	4096KB (I+D) on chip
Other Cache:	None
Memory:	2 GB, DDR266, 2.5-3-3, (4x512MB DIMMs)
Disk Subsystem:	1x 40GB IDE, 5400rpm
Other Hardware:	None

Software

Operating System:	Red Hat Enterprise Linux ES release 3
Compiler:	Intel(R) C++ Compiler for Linux 8.0 (Build 20040412Z) MicroQuill SmartHeap Library 7.1 (www.microquill.com)
File System:	ext2
System State:	Multi-user, 2.4.21 smp kernel

Notes/Tuning Information

```
Portability Flags:
      176.gcc: -Dalloca=_alloca -DUSG
   186.crafty: -DLINUX_i386
      252.eon: -DHAS_ERRLIST
      252.eon: srcalt=fmax_errno
  253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
               -DSPEC_CPU2000_GLIBC22
      254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
               -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
   255.vortex: srcalt=closed_files
HyperThreading disabled in BIOS

INT Baseline optimization flags:
   C programs: PASS1= -xN -prof_gen PASS2= -xN -fast -prof_use
 C++ programs: PASS1= -xN -prof_gen PASS2= -xN -fast -ansi_alias -prof_use
INT Peak optimization flags:
      164.gzip: basepeak=yes
       175.vpr: basepeak=yes
       176.gcc: basepeak=yes
```

CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION Computer Systems

BX41 (3GHz Xeon MP processor w. 4MB L3 cache)

SPECint_rate2000 = 60.0

SPECint_rate_base2000 = 60.0

SPEC license #: 2697	Tested by: ION	Test date: May-2004	Hardware Avail: May-2004	Software Avail: Apr-2004

Notes/Tuning Information (Continued)

```
      181.mcf: basepeak=yes
    186.crafty: basepeak=yes
    197.parser: basepeak=yes
       252.eon: basepeak=yes
   253.perlbmk: basepeak=yes
       254.gap: basepeak=yes
    255.vortex: basepeak=yes
     256.bzip2: basepeak=yes
     300.twolf: PASS1= -xN -prof_gen PASS2= -xN -ipo -Oa -O3 -prof_use
Extra Library: -L${SH_PATH} -lsmartheap  (SH_PATH is path to SmartHeap Library)
```