



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers CELSIUS M420

SPECint2000 = 1501
SPECint_base2000 = 1443

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: Jun-2004 Hardware Avail: Jun-2004 Software Avail: Mar-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	124	1125	125	1123	
175.vpr	1400	140	998	141	996	
176.gcc	1100	60.5	1820	60.1	1831	
181.mcf	1800	139	1299	139	1297	
186.crafty	1000	79.0	1266	79.0	1266	
197.parser	1800	136	1328	136	1328	
252.eon	1300	79.8	1630	66.6	1951	
253.perlbmk	1800	111	1624	102	1761	
254.gap	1100	60.5	1819	61.0	1804	
255.vortex	1900	74.8	2542	74.8	2542	
256.bzip2	1500	137	1093	135	1109	
300.twolf	3000	219	1370	179	1678	

Hardware

CPU: Pentium 4 processor (3.4E GHz, 800 MHz bus)
CPU MHz: 3400
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (HT Technology disabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 2048 MB (4 512 MB PC3200 DDR ECC modules)
Disk Subsystem: Maxtor 6Y160M0 (Serial ATA 7200 rpm)
Other Hardware:

Software

Operating System: Windows XP Professional, Service Pack 1
Compiler: Intel(R) C++ Compiler, Version 8.0,
- Build 20040318Z Package ID: W_CC_PC_8.0.048
Microsoft Visual Studio .NET 7.0 (for libraries)
MicroQuill SmartHeap Library 6.03a
File System: FAT32
System State: Default

Notes/Tuning Information

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Feedback optimization:

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:

for C programs except 252.eon:
-QxP -fast -Qansi_alias +FDO
for C++ program 252.eon:
-QxP -fast -GX -GR

Peak Tuning Flags:

164.gzip: -QxP -fast -Qansi_alias -Oa +FDO
175.vpr: -QxP -fast -Qansi_alias +FDO
176.gcc: -QxP -fast -Qansi_alias +FDO
181.mcf: -QxP -fast -Qansi_alias +FDO



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS M420

SPECint2000 =	1501
SPECint_base2000 =	1443

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jun-2004 | Hardware Avail: Jun-2004 | Software Avail: Mar-2004

Notes/Tuning Information (Continued)

```
186.crafty: -QxP -fast -Qansi_alias -Oa +FDO
197.parser: -QxP -fast -Qansi_alias +FDO
252.eon: -QxP -O2 -Qipo +FDO
253.perlbmk: -QxP -fast -Qansi_alias +FDO shlw32M.lib
254.gap: -QxP -fast -Qunroll11 -Zp8 +FDO
255.vortex basepeak=yes
256.bzip2: -fast -Oa -Qunroll11 +FDO
300.twolf: -QxP -fast -O3 +FDO shlw32M.lib
```

Extra Libraries:

shlw32M.lib = Microquill SmartHeap Library 6.03a
see www.microquill.com

The system bus runs at 800 MHz

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>