CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECfp_rate2000 = 70.0

SPECfp_rate_base2000 = 61.5

SPEC license #: 6 | Tested by: Sun Microsystems, Santa Clara | Test date: Jul-2004 | Hardware Avail: Jul-2004 | Software Avail: Jul-2004



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	107	69.6	4	86.8	85.6
171.swim	4	163	88.1	4	150	95.9
172.mgrid	4	223	37.5	4	152	55.0
173.applu	4	183	53.4	4	147	66.1
177.mesa	4	77.7	83.6	4	71.8	90.5
178.galgel	4	119	113	4	109	123
179.art	4	345	34.9	4	178	67.9
183.equake	4	114	52.8	4	108	55.8
187.facerec	4	97.2	90.7	4	97.2	90.7
188.ammp	4	170	60.0	4	167	61.1
189.lucas	4	140	66.1	4	140	66.2
191.fma3d	4	154	63.1	4	154	63.1
200.sixtrack	4	150	34.1	4	150	34.1
301.apsi	4	180	67.1	4	179	67.3

Hardware

CPU:	AMD Opteron (TM) 850
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	4 cores, 4 chips, 1 core/chip
CPU(s) orderable:	1,2,4
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip
Secondary Cache:	1024KB (I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	16x1GB, PC2700 CL2.5 DDR SDRAM ECC Registered
Disk Subsystem:	SCSI, 73GB, 10K RPM
Other Hardware:	None

Software

Operating System:	SuSE Linux 8.0 SLES 64 bit (SP3)
Compiler:	PathScale EKO Compiler Suite, Release 1.1 SuSE optional gcc 3.3 (from SLES8 SP3) PGI Fortran 5.2 (build 5.2-0E) AMD Core Math Library (Version 2.0) for AMD64
File System:	Linux/ext3
System State:	Multi-user, Run level 3

Notes/Tuning Information

```
A two-pass compilation method is used where indicated:
  +PSFDO indicates PathScale feedback
           PASS1: -fb_create fbdata
           PASS2: -fb_opt    fbdata
  +ACML is the AMD Core Math Library V2.0

Compilers:
   C:       pathcc  (PathScale C) unless otherwise noted
   Fortran: pathf90 (PathScale f90) unless otherwise noted
If other compilers are used, they are indicated as:
   gcc:   Gnu C
   pgf90: PGI Fortran

Floating Point base tuning:
 Fortran: pgf90 -fastsse  -Mipa=fast -Msmart
 C:       pathcc -Ofast -WOPT:mem_opnds=on +PSFDO
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
Floating Point peak tuning:
168.wupwise:  pgf90 -fastsse -Mipa=fast,inline -Msmart
171.swim:     -Ofast -OPT:ro=3 -LNO:fusion=2:prefetch=2
172.mgrid:    -O3 -OPT:Ofast
              -LNO:fusion=2:blocking=off:ou_max=5:sclrze=off:prefetch=2
              -OPT:unroll_times=8:unroll_size=256:ro=3
              -CG:gcm=off:cflow=off
173.applu:    -O3 -ipa
              -LNO:fusion=2:interchange=OFF:blocking=OFF:ou_prod_max=10
              :ou_max=5:prefetch=2 -OPT:IEEE_arith=1:ro=3:unroll_size=0
             -TENV:X=4 -WOPT:mem_opnds=on:retype_expr=on:val=0 -CG:local_fwd_sched=on
177.mesa:     -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +PSFDO
178.galgel:   pgf90 -fastsse -Mipa=fast -mp +ACML
              RM_SOURCES=lapak.f90 ONESTEP
179.art:      -O3 -OPT:Ofast -fno-math-errno -m32 +PSFDO
183.equake:   gcc -DSPEC_CPU2000_LP64 -O3 -funroll-all-loops -ffast-math
              -finline-limit=2000 ONESTEP
187.facerec:  basepeak=true
188.ammp:     -O3 -OPT:alias=disjoint:unroll_times=8:Ofast:ro=3
              -fno-math-errno -TENV:X=4 +PSFDO
189.lucas:  pgf90 -fastsse -Mipa=fast,inline -Msmart
191.fma3d:  basepeak=true
200.sixtrack: basepeak=true
301.apsi:     -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0:blocking=off
              -IPA:linear=on:plimit=525

Portability:
178.galgel:     -Mfixed

Notes:
     BIOS build 2.1.0.9E, default setting was used.
```