CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V240 (1503MHz)

SPECint_rate2000 = 18.4

SPECint_rate_base2000 = 16.2

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Dec-2004 | Hardware Avail: Jan-2005 | Software Avail: Jan-2005



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	211	15.4	2	188	17.3
175.vpr	2	233	13.9	2	227	14.3
176.gcc	2	157	16.3	2	124	20.7
181.mcf	2	522	8.00	2	304	13.8
186.crafty	2	121	19.1	2	102	22.8
197.parser	2	294	14.2	2	261	16.0
252.eon	2	134	22.6	2	133	22.7
253.perlbmk	2	237	17.6	2	219	19.0
254.gap	2	182	14.0	2	162	15.7
255.vortex	2	145	30.5	2	139	31.7
256.bzip2	2	241	14.4	2	234	14.9
300.twolf	2	402	17.3	2	373	18.6

Hardware

CPU:	UltraSPARC IIIi
CPU MHz:	1503
FPU:	Integrated
CPU(s) enabled:	2 cores, 2 chips, 1 core/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	32KBI+64KBD on chip
Secondary Cache:	1MB(I+D) on chip
L3 Cache:	None
Other Cache:	None
Memory:	8GB 16-way interleaved
Disk Subsystem:	1 x 73GB
Other Hardware:	None

Software

Operating System:	Solaris 10
Compiler:	Sun Studio 9
File System:	ufs
System State:	Multi-User

Notes/Tuning Information

```
Compiler invocation:
  C: cc
  CXX: CC

Integer base flags:
  -fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:
 ONESTEP=yes and feedback for all benchmarks

 164.gzip:    -xO5 -xbuiltin=%all -xtarget=native -xalias_level=std
              -xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100
 175.vpr:     -fast -xalias_level=std -xipo=2
              -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100,
               -Qeps:do_spec_load=1 -lmopt -lm
 176.gcc:     -fast -xipo=2 -ll2amm
 181.mcf:     -fast -xipo=2 -xprefetch_level=3 -Wc,-Qeps:enabled=1
              -W2,-Apf:llist=3:noinnerllist
 186.crafty:  -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
              Feedback adds -xlinkopt in PASS2
```

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 197.parser:  -fast -xipo=2 -xalias_level=strong
              -Wc,-Qgsched-T6,-Qipa:valueprediction
 252.eon:     -fast -xipo=2 -xalias_level=compatible -noex
              -Qoption cg -Qeps:enabled=1,-Qeps:ws=32
 253.perlbmk: -xO5 -xtarget=native -xmemalign=4s -xipo
              -Wc,-Qeps:enabled=1,-Qeps:ws=8 -xalias_level=std -xsafe=mem
              -Wc,-Qiselect-funcalign=32,-Qicache-chbab=1
              -Wc,-Qiselect-sw_pf_tbl_th=20,-Qeps:do_spec_load=1
              -xprefetch=no
 254.gap:     -fast -xipo=2 -xalias_level=strong -xvector -xprefetch_level=3
              -W2,-Abcopy
 255.vortex:  -fast -xrestrict -xipo=2
              -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
              -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
              -Qiselect-funcalign=32,-Qpeep-Sh0 -ll2amm
 256.bzip2:   -fast -xipo=2 -xalias_level=strong -xrestrict
              -Wc,-Qeps:enabled=1 -xsafe=mem -Qeps:rp_filtering_margin=99
 300.twolf:   -fast -xalias_level=strong -xsafe=mem -xipo=2
              -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

Feedback is done as follows, unless otherwise noted:
 fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
 PASS1:     -xprofile=collect:./feedback
 PASS2:     -xprofile=use:./feedback

Portability:
 176.gcc:     -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
 186.crafty:  -DSUN
 252.eon:     -library=iostream
              srcalt=fmax_errno
 253.perlbmk: -DSPEC_CPU2000_SOLARIS
 254.gap:     -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
              -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

Shell Environments:
  Stack size set to unlimited via "ulimit -s unlimited"
  MPSSHEAP=512K
  MPSSSTACK=512K
  LD_PRELOAD=mpss.so.1

Kernel Parameters (/etc/system):
 autoup=900
 tune_t_fsflushr=1
Processes were bound to CPUs using submit=pbind
```