CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R510 (3.6 GHz Intel Xeon)

SPECint2000 = 1679

SPECint_base2000 = 1675

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2005 | Hardware Avail: May-2005 | Software Avail: Oct-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	117	1194	117	1194
175.vpr	1400	122	1144	120	1162
176.gcc	1100	55.2	1994	55.2	1994
181.mcf	1800	104	1733	104	1733
186.crafty	1000	74.7	1339	74.7	1339
197.parser	1800	124	1453	124	1453
252.eon	1300	57.7	2252	57.6	2257
253.perlbmk	1800	87.0	2069	86.9	2072
254.gap	1100	58.0	1895	58.0	1895
255.vortex	1900	69.4	2739	69.4	2739
256.bzip2	1500	122	1226	122	1233
300.twolf	3000	167	1797	167	1797



Hardware

CPU:	Intel Xeon (3.6 GHz, 2MB L2, 800MHz system bus)
CPU MHz:	3600
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	12KB(I) micro-ops + 16KB(D) on chip
Secondary Cache:	2048KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	6 x 512MB ECC DDR-333 SDRAM
Disk Subsystem:	1 x 120GB 7200RPM SATA HDD
Other Hardware:	

Software

Operating System:	Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler:	Intel C++ Compiler 8.1 Build 20041019Z Microsoft Visual Studio .Net 2003(7.1.3091, for libraries) SmartHeap Library Version 7.4 from http://www.microquill.com/
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon:   Approved stdcpp src.alt used
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip:     basepeak=yes
175.vpr:      -fast -Qansi_alias +FDO
176.gcc:      basepeak=yes
181.mcf:      basepeak=yes
186.crafty:   basepeak=yes
197.parser:   -fast -Qansi_alias  +FDO
252.eon:      -fast +FDO
253.perlbmk:  -fast -Qansi_alias +FDO shlW32M.lib
254.gap:      basepeak=yes
255.vortex    basepeak=yes
```

CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R510 (3.6 GHz Intel Xeon)

SPECint2000 = 1679

SPECint_base2000 = 1675

SPEC license #: 97	Tested by: Acer Incorporated	Test date: May-2005	Hardware Avail: May-2005	Software Avail: Oct-2004

Notes/Tuning Information (Continued)

```
256.bzip2:   -fast -Oa -Qunroll1 +FDO
300.twolf:    -fast -O3 +FDO shlW32M.lib
Enable hardware prefetching and adjacent cache line prefetch BIOS setting
Product description located at http://www.acer.com
```