CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY BX630, AMD Opteron (TM) 252

SPECint2000 = 1817
SPECint_base2000 = 1668

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Jan-2006 | Software Avail: Mar-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	98.3	1424	98.3	1424
175.vpr	1400	100	1398	97.0	1443
176.gcc	1100	57.6	1910	57.9	1899
181.mcf	1800	159	1132	130	1384
186.crafty	1000	59.2	1690	54.1	1848
197.parser	1800	112	1614	112	1614
252.eon	1300	64.4	2018	45.8	2840
253.perlbmk	1800	106	1703	97.4	1849
254.gap	1100	60.8	1811	60.8	1811
255.vortex	1900	71.2	2670	64.9	2929
256.bzip2	1500	110	1369	107	1399
300.twolf	3000	173	1732	145	2070



Hardware

CPU:	AMD Opteron (TM) 252 processor (2.60 GHz)
CPU MHz:	2600
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	64KBI + 64KBD on chip, per core
Secondary Cache:	1024KB (I+D) on chip, per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x1024MB DDR-RAM PC3200R CL3-3-3
Disk Subsystem:	Western Digital WD2500 (SATA, 7.2krpm)
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1
Compiler:	Intel C++ 8.0 Build 20040318Z (for 32-bit applications), Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries), SmartHeap Library Version 8.0 from http://www.microquill.com
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
GENERAL
+FDO: PASS1= -Qprof_gen  PASS2= -Qprof_use

Portability flags
   176.gcc:     -Dalloca=_alloca /F10000000
   186.crafty:  -DNT_i386
   253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
   254.gap:     -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags
   for C programs:   -fast -arch:SSE2 -Oi- +FDO
   for C++ programs: -fast -GX -GR +FDO

Peak tuning flags
   164.gzip:    basepeak=yes
   175.vpr:     -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000,
                -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
   176.gcc:     -fast -arch:SSE2 -Oi- -Qunroll3 +FDO shlw32M.lib
   181.mcf:     -fast -QaxN +FDO shlw32M.lib
   186.crafty:  -fast -arch:SSE2 +FDO ONESTEP=yes shlw32M.lib
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
    197.parser:  basepeak=yes
    252.eon:     -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000,
                 -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
    253.perlbmk: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes shlw32M.lib
    254.gap:     basepeak=yes
    255.vortex:  -fast -arch:SSE -Oi- -Qoption,c,-ip_ninl_max_stats=2000,
                 -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
    256.bzip2:   -fast -Qunroll2 shlw32M.lib
    300.twolf:   -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib


boot options:  /Execute /NOPAE
               /USEPMTIMER
BIOS settings: Memory Timing: 1T
               DRAM Bank Interleave=AUTO

This result was measured with 32-bit binaries using the 32-bit version of
the operating system.

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```