CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1955 (Intel Xeon processor 5050, 3.00GHz)

SPECfp_rate2000 = 43.8

SPECfp_rate_base2000 = 43.8

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: Mar-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	122	60.6	4	122	60.6
171.swim	4	472	30.5	4	472	30.5
172.mgrid	4	298	28.0	4	298	28.0
173.applu	4	314	31.1	4	314	31.1
177.mesa	4	92.3	70.4	4	92.3	70.4
178.galgel	4	145	92.7	4	145	92.7
179.art	4	109	110	4	109	110
183.equake	4	213	28.3	4	213	28.3
187.facerec	4	180	49.0	4	180	49.0
188.ammp	4	221	46.1	4	221	46.1
189.lucas	4	308	30.1	4	308	30.1
191.fma3d	4	281	34.7	4	281	34.7
200.sixtrack	4	187	27.4	4	187	27.4
301.apsi	4	270	44.7	4	270	44.7

Hardware

CPU:	Intel Xeon processor 5050 (667MHz system bus)
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	12K(I) micro-ops + 16KB(D) on chip, per core
Secondary Cache:	2048KB(I+D) on chip, per core
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8 x 1GB 533MHz ECC CL4 DDR2 FB-DIMM
Disk Subsystem:	1 x 73GB SAS 10000 RPM
Other Hardware:	None

Software

Operating System:	Red Hat Enterprise Linux 4 Advanced Server Update 3 EM64T
Compiler:	Intel C++ and Fortran Compiler 9.0 for EM64T Builds 20060120 and 20051201
File System:	ext3
System State:	Runlevel 3

Notes/Tuning Information

```
GENERAL
 ONESTEP=yes for all benchmarks
 +FDO implies feedback-directed optimization PASS1: -prof_gen   PASS2: -prof_use
PORTABILITY FLAGS
 -DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI for fixed-format Fortran
BASE TUNING
 Baseline optimizations for C and Fortran: -fast +FDO
PEAK TUNING
 basepeak=yes set for all benchmarks
```