CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon 5130 processor, 2.0 GHz

SPECfp_rate2000 = 69.2

SPECfp_rate_base2000 = 69.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	75.4	98.5	4	75.4	98.5
171.swim	4	273	52.6	4	273	52.6
172.mgrid	4	176	47.4	4	176	47.4
173.applu	4	193	50.5	4	193	50.5
177.mesa	4	69.1	94.0	4	69.1	94.0
178.galgel	4	77.9	173	4	77.9	173
179.art	4	61.5	196	4	61.5	196
183.equake	4	120	50.3	4	120	50.3
187.facerec	4	101	87.4	4	101	87.4
188.ammp	4	161	63.4	4	161	63.4
189.lucas	4	178	52.1	4	178	52.1
191.fma3d	4	184	52.9	4	184	52.9
200.sixtrack	4	146	35.0	4	146	35.0
301.apsi	4	223	54.2	4	223	54.2

Hardware

CPU:	Intel Xeon 5130 processor (2.0 GHz, 4MB SLC, 1333 MHz system bus)
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2
Parallel:	No
Primary Cache:	32KB(I) + 32KB(D) on chip, per core
Secondary Cache:	4096KB(I+D) on chip, per chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8x1024 MB DDRII-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem:	Seagate ST336754SS (SAS, 15.4krpm, 36GB)
Other Hardware:	none

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 9 with SP3 Kernel 2.6.5-7.244-smp on an x86_64
Compiler:	Intel C++ and Fortran Compiler 9.0 for EM64T Build 20060120 (for 64-bit applications)
File System:	ext2
System State:	Multi-user run level 3

Notes/Tuning Information

```
GENERAL
+FDO implies feedback-directed optimization
PASS1: -prof_gen  PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
   for Fortran and C programs: -fast +FDO

Peak tuning flags
   same as baseline (basepeak=true set globally)
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

This result was measured on the PRIMERGY TX300 S3. The PRIMERGY TX300 S3 and the PRIMERGY RX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see: http://www.fujitsu-siemens.com/countries