



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Advanced Micro Devices**  
Tyan Thunder K9HM (S3992), AMD Opteron (TM) 2210

SPECfp2000 = **1746**  
SPECfp\_base2000 = **1578**

SPEC license #: 49 Tested by: AMD Austin, TX Test date: Jul-2006 Hardware Avail: Sep-2006 Software Avail: Jan-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	76.8	2085	67.3	2378	
171.swim	3100	126	2456	120	2585	
172.mgrid	1800	133	1356	115	1561	
173.applu	2100	129	1623	115	1821	
177.mesa	1400	102	1375	87.4	1601	
178.galgel	2900	113	2566	98.5	2943	
179.art	2600	116	2250	85.3	3046	
183.earthquake	1300	87.6	1484	80.8	1608	
187.facerec	1900	87.9	2163	89.3	2127	
188.amp	2200	197	1116	183	1200	
189.lucas	2000	106	1889	92.6	2159	
191.fma3d	2100	160	1308	160	1313	
200.sixtrack	1100	181	606	174	634	
301.apsi	2600	210	1240	197	1319	

### Hardware

CPU: AMD Opteron (TM) 2210  
 CPU MHz: 1800  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD on chip per core  
 Secondary Cache: 1024KB (I+D) on chip per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4x512MB, DDR2-667 CL4 ECC Reg  
 Disk Subsystem: IDE, 120 GB  
 Other Hardware: None

### Software

Operating System: SuSE Linux Enterprise Server 9 SP3 (64-bit)  
 Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.3  
 File System: Linux/ext3  
 System State: Multi-user, run level 3

## Notes/Tuning Information

+FDO: PASS1= -fb\_create fbdata PASS2= -fb\_opt fbdata  
 +ACML means -L<acml2.7.0-install-dir>/pathscale64/lib -lacml,  
 which causes linking with AMD Core Math Library V2.7.0

### Baseline optimization

C programs: -Ofast -WOPT:mem\_opnds=on +FDO  
 Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast\_complex=on +FDO  
 Portability Flags:  
 178.galgel: -fixedform

### Peak Tuning:

168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3  
 -OPT:unroll\_times\_max=8:unroll\_size=128:IEEE\_NaN\_Inf=off:ro=3  
 -IPA:linear=on:plimit=50000:callee\_limit=5000  
 -INLINE:aggressive=on  
 171.swim: -Ofast -CG:local\_fwd\_sched=on -LNO:fusion=2 -m3dnow



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices  
Tyan Thunder K9HM (S3992), AMD Opteron (TM) 2210

SPECfp2000 = 1746  
SPECfp\_base2000 = 1578

SPEC license #: 49 | Tested by: AMD Austin, TX | Test date: Jul-2006 | Hardware Avail: Sep-2006 | Software Avail: Jan-2006

## Notes/Tuning Information (Continued)

```

172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_arith=3:unroll_size=200
           -LNO:fusion=2:fission=1:blocking=off:prefetch_ahead=2
           -WOPT:mem_opnds=on:aggstr=0
173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
           -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3 +FDO
177.mesa:  -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on -WOPT:mem_opnds=on +FDO
178.galgel: -Ofast -OPT:fast_complex=on +ACML +FDO
           RM_SOURCES=lapak.f90
179.art:   -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.quake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec: -Ofast -LNO:fusion=2
           -OPT:fast_complex=on:IEEE_NaN_Inf=off:unroll_size=0 +FDO
188.ammp:  -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
           -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
           -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000:early_intrinsics=on
           -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:  -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

system can be built using a standard ATX case and a Zippy 700W PSL-6701P power supply  
Half memory slots populated on CPU in dual channel configuration