



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Intel(R) Corporation

Intel(R) DG965WH motherboard( 2.67 GHz, Intel(R) Core(TM) 2 processor E6700)

SPECint\_rate2000 = 59.4

SPECint\_rate\_base2000 = 59.3

SPEC license #: 13 Tested by: Intel Corporation Test date: Jul-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	86.6	37.5	2	86.2	37.7
175.vpr	2	76.7	42.4	2	75.4	43.1
176.gcc	2	38.8	65.7	2	38.8	65.7
181.mcf	2	68.9	60.6	2	68.9	60.6
186.crafty	2	41.1	56.5	2	41.2	56.3
197.parser	2	92.5	45.1	2	92.7	45.1
252.eon	2	37.8	79.7	2	37.7	80.0
253.perlbnk	2	56.3	74.2	2	56.5	73.9
254.gap	2	41.6	61.4	2	41.6	61.4
255.vortex	2	43.1	102	2	43.1	102
256.bzip2	2	77.4	45.0	2	77.1	45.1
300.twolf	2	100.0	69.6	2	100.0	69.6

### Hardware

CPU: Intel(R) Core(TM) 2 processor E6700( 2.67 GHz, 1066 MHz bus)  
CPU MHz: 2667  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 32KBI + 32KBD per core  
Secondary Cache: 4MB(I+D) shared, per chip  
L3 Cache: None  
Other Cache: None  
Memory: 2 GB (2 1GB Corsair TWIN2X2048-8500C5 DDR2 1066 CL5-5-5 DIMMs)  
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)  
Other Hardware: ATI Radeon X1900 XTX PCI express graphics card

### Software

Operating System: Windows XP Professional SP2  
Compiler: Intel C++ Compiler 9.1 for 32-bit applications  
Build 20060323Z Package ID: W\_CC\_P\_9.1.020  
Microsoft Visual Studio 2005(for libraries)  
SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlW32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlW32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard( 2.67 GHz, Intel(R) Core(TM) 2 processor E6700)

SPECint\_rate2000 = 59.4

SPECint\_rate\_base2000 = 59.3

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO

300.twolf: -fast -O3 +FDO shlw32M.lib

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 07/2006

<http://www.intel.com/products/motherboard/dg965wh/index.htm>

The system bus runs at 1066 MHz