CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D945GPM motherboard(3.8 GHz, Intel(R) Pentium(TM) 4 processor 670)

SPECfp_rate2000 = 25.1

SPECfp_rate_base2000 = 25.1

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	72.5	51.2	2	72.5	51.2
171.swim	2	247	29.1	2	247	29.2
172.mgrid	2	201	20.7	2	202	20.7
173.applu	2	222	22.0	2	222	22.0
177.mesa	2	171	19.0	2	171	19.0
178.galgel	2	169	39.7	2	170	39.6
179.art	2	147	40.9	2	147	40.9
183.equake	2	82.5	36.6	2	82.2	36.7
187.facerec	2	158	27.9	2	158	28.0
188.ammp	2	328	15.6	2	331	15.4
189.lucas	2	179	25.9	2	179	25.9
191.fma3d	2	231	21.1	2	231	21.1
200.sixtrack	2	244	10.5	2	239	10.7
301.apsi	2	297	20.3	2	297	20.3

Hardware

CPU:	Intel(R) Pentium(TM) 4 processor 670(3.8 GHz, 800 MHz bus)
CPU MHz:	3800
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	12k micro-opsI + 16KBD per core, on chip
Secondary Cache:	2MB(I+D) per chip, on chip
L3 Cache:	None
Other Cache:	None
Memory:	2 GB (2 1GB Micron DDR2 667 CL5-5-5 DIMMs)
Disk Subsystem:	Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware:	ATI Radeon X850 XT PCI express graphics card

Software

Operating System:	Windows XP Professional SP2
Compiler:	Intel C++ and Fortran Compiler 9.1 for 32-bit applications Build 20060323Z Package ID: W_FC_P_9.1.020 Microsoft Visual Studio 2005(for libraries) SmartHeap Library Version 8.0 from http://www.microquill.com/
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=  -Qprof_gen  PASS2=-Qprof_use
Base tuning for Fortran programs:  -fast -Qansi_alias +FDO
Base tuning for C programs:  -fast    +FDO shlW32M-80.lib
Portability:
178.galgel:   -FI /F32000000
Peak tuning:
168.wupwise:  -fast -Qansi_alias +FDO
171.swim:     -fast -Qansi_alias +FDO
172.mgrid:    -fast -Qansi_alias +FDO
173.applu:  basepeak=yes
177.mesa:   basepeak=yes
178.galgel:   -fast -Qansi_alias +FDO
179.art:      basepeak=yes
183.equake:   -QxP -Oa -Qrcd -Qipo  +FDO  shlW32M-80.lib
187.facerec:  -fast -Qunroll1 -Qscalar_rep- +FDO
188.ammp:     -fast -Oa +FDO  shlW32M-80.lib
189.lucas:    -fast -Qprefetch- +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
191.fma3d:    basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi:     -fast +FDO
Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
Product description located as of 07/2006
http://www.intel.com/products/motherboard/dg965wh/index.htm
The system bus runs at 800 MHz
```