CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS M450 (Intel Core 2 Duo processor E6600)

SPECfp2000 = 2513

SPECfp_base2000 = 2506

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	40.8	3919	40.7	3928
171.swim	3100	116	2666	117	2658
172.mgrid	1800	115	1564	115	1563
173.applu	2100	105	1991	105	1991
177.mesa	1400	61.8	2264	61.7	2271
178.galgel	2900	50.3	5769	50.3	5771
179.art	2600	30.9	8404	30.9	8413
183.equake	1300	40.1	3244	40.1	3239
187.facerec	1900	73.2	2595	73.2	2594
188.ammp	2200	128	1722	122	1797
189.lucas	2000	80.2	2493	80.2	2493
191.fma3d	2100	113	1863	113	1859
200.sixtrack	1100	114	962	114	962
301.apsi	2600	156	1665	156	1665



Hardware

CPU:	Intel Core 2 Duo processor E6600
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1
Parallel:	No
Primary Cache:	32KB(I) + 32KB(D) on chip, per core
Secondary Cache:	4096KB(I+D) on chip
L3 Cache:	N/A
Other Cache:	N/A
Memory:	4x 1GB PC2-5300 5-5-5 2Rank SDRAM
Disk Subsystem:	1 x 160GB SATA 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows XP Professional, Service Pack 2
Compiler:	Intel(R) C++ Compiler for 32-bit app., Version 9.1, - Build 20060519Z Package ID: W_CC_P_9.1.025 Intel(R) Fortran Compiler for 32-bit app., Version 9.1, - Build 20060519Z Package ID: W_FC_P_9.1.025 Microsoft Visual Studio .NET 2003 (for libraries) MicroQuill SmartHeap Library, Version 8 (shlW32M.lib)
File System:	FAT32
System State:	Default

Notes/Tuning Information

```
Portability flags:
 178.galgel:  -FI /F32000000

Feedback optimization:
  +FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:
 for C programs:
 -fast +FDO shlW32M.lib
 for Fortran programs:
 -fast +FDO shlW32M.lib

Peak Tuning Flags:
 173.applu:      basepeak=yes
 168.wupwise:  -fast +FDO
 171.swim:     -fast +FDO
 172.mgrid:    -fast +FDO
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
 173.applu:    basepeak=yes
 177.mesa:     -fast +FDO ONESTEP=yes
 178.galgel:   -fast +FDO
 179.art:      -fast +FDO shlW32M.lib
 183.equake:   -fast +FDO shlW32M.lib
 187.facerec:  -fast +FDO
 188.ammp:     -fast +FDO
 189.lucas:    basepeak=yes
 191.fma3d:    -fast +FDO
 200.sixtrack: -fast +FDO
 301.apsi:     -fast +FDO

Extra Libraries:
 shlW32M.lib = Microquill SmartHeap Library 8
 see www.microquill.com

The system bus runs at 1066 MHz

For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```