



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM Corporation

IBM System X 3500 (2.33 GHz Xeon 5140, 4MB L2 Cache)

SPECfp\_rate2000 = --

SPECfp\_rate\_base2000 = 72.3

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	73.9	100			
171.swim	4	270	53.3			
172.mgrid	4	172	48.7			
173.applu	4	194	50.2			
177.mesa	4	64.2	101			
178.galgel	4	68.8	196			
179.art	4	64.4	187			
183.quake	4	92.9	64.9			
187.facerec	4	103	86.0			
188.amp	4	163	62.8			
189.lucas	4	179	51.8			
191.fma3d	4	182	53.4			
200.sixtrack	4	120	42.4			
301.apsi	4	225	53.5			

### Hardware

CPU: Intel Xeon processor 5140 (2.33 GHz, 1333 MHz bus)  
 CPU MHz: 2333  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1, 2  
 Parallel: No  
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)  
 Secondary Cache: 4096KB(I+D) on chip (per chip)  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8 x 1024 MB ECC PC2-5300F  
 Disk Subsystem: 80GB SATA 10K RPM  
 Other Hardware:

### Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)  
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications  
 Build 20060323Z  
 Microsoft Visual Studio 2005(for libraries)  
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
```

This result was measured on an IBM System X 3400. IBM System X 3500 and IBM System X 3400 are electronically equivalent.