CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3400 (1.86 GHz Xeon E5320, 8MB L2 Cache)

SPECint_rate2000 = --

SPECint_rate_base2000 = 147

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2006 | Hardware Avail: Dec-2006 | Software Avail: Mar-2006



Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	127	102			
175.vpr	8	122	106			
176.gcc	8	62.3	164			
181.mcf	8	153	109			
186.crafty	8	57.8	160			
197.parser	8	139	120			
252.eon	8	53.6	225			
253.perlbmk	8	82.8	202			
254.gap	8	92.9	110			
255.vortex	8	68.5	257			
256.bzip2	8	125	111			
300.twolf	8	141	198			

Hardware

CPU:	Intel Xeon processor E5320 (1.86 GHz, 1066 MHz bus)
CPU MHz:	1866
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1, 2 chips
Parallel:	No
Primary Cache:	32KB(I) + 32KB(D) on chip (per core)
Secondary Cache:	8MB(I+D) on chip, per chip (4MB shared per 2 cores)
L3 Cache:	N/A
Other Cache:	N/A
Memory:	8 x 1024 MB ECC PC2-5300F
Disk Subsystem:	80GB SATA 10K RPM
Other Hardware:	

Software

Operating System:	Windows Server 2003 Enterprise Edition (32-bit)
Compiler:	Intel C++ Compiler 9.1 for 32-bit applications Build 20060323Z Microsoft Visual Studio 2005(for libraries) SmartHeap Library Version 8.0 from http://www.microquill.com/
File System:	NTFS
System State:	Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlW32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon:     -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

This result was measured on an IBM System X 3400.   IBM System X 3400 and IBM System
X 3500 are electronically equivalent.
```