# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL140 G3 (3.0 GHz, Intel Xeon processor 5160)

SPECint_rate2000 = 62.5

SPECint_rate_base2000 = 62.3

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Nov-2006 | Hardware Avail: Jun-2006 | Software Avail: Oct-2006




| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|---|---|---|---|---|---|---|
| 164.gzip | 2 | 77.1 | 42.1 | 2 | 76.6 | 42.4 |
| 175.vpr | 2 | 77.9 | 41.7 | 2 | 75.2 | 43.2 |
| 176.gcc | 2 | 38.7 | 65.9 | 2 | 38.7 | 65.9 |
| 181.mcf | 2 | 72.4 | 57.7 | 2 | 72.8 | 57.4 |
| 186.crafty | 2 | 36.5 | 63.5 | 2 | 36.6 | 63.4 |
| 197.parser | 2 | 83.2 | 50.2 | 2 | 82.8 | 50.5 |
| 252.eon | 2 | 32.9 | 91.6 | 2 | 33.0 | 91.4 |
| 253.perlbmk | 2 | 51.8 | 80.6 | 2 | 52.0 | 80.3 |
| 254.gap | 2 | 41.6 | 61.3 | 2 | 41.3 | 61.8 |
| 255.vortex | 2 | 45.4 | 97.2 | 2 | 45.4 | 97.2 |
| 256.bzip2 | 2 | 76.7 | 45.4 | 2 | 76.7 | 45.4 |
| 300.twolf | 2 | 86.5 | 80.4 | 2 | 86.5 | 80.5 |

### Hardware

| | |
|---|---|
| CPU: | Intel Xeon processor 5160 (1333 MHz system bus) |
| CPU MHz: | 3000 |
| FPU: | Integrated |
| CPU(s) enabled: | 2 cores, 1 chip, 2 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Parallel: | No |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 4 MB I+D on chip per chip |
| L3 Cache: | N/A |
| Other Cache: | N/A |
| Memory: | 8 GB (8 x 1 GB PC2-5300F) |
| Disk Subsystem: | 2 x 36 GB 15 K SAS |
| Other Hardware: | |

### Software

| | |
|---|---|
| Operating System: | Windows Server 2003 Enterprise SP1 |
| Compiler: | Intel C++ Compiler for 32-bit applications, (version 9.1 Build 20060816Z)<br>Microsoft Visual Studio .NET 7.0.9466 (for libraries)<br>MicroQuill Smartheap Library 8.0 |
| File System: | NTFS |
| System State: | Default |

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen  PASS2=-Qprof_use
Base tuning for C programs:   -fast         +FDO  ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
  176.gcc: -Dalloca=_alloca /F10000000
  186.crafty: -DNT_i386
  253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
  254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
  164.gzip:     -fast               +FDO  ONESTEP=yes
  175.vpr:      -fast               +FDO  ONESTEP=yes
  176.gcc:      basepeak=1
  181.mcf:      -fast               +FDO  ONESTEP=yes shlw32M.lib
  186.crafty:   -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  197.parser:   -fast               +FDO  ONESTEP=yes
  252.eon:      -fast               +FDO
  253.perlbmk:  -fast -Oa           +FDO  ONESTEP=yes shlw32M.lib
  254.gap:      -fast               +FDO  ONESTEP=yes
  255.vortex:   -fast               +FDO  ONESTEP=yes shlw32M.lib
  256.bzip2:    basepeak=1
```

Copyright ©1999-2005, Standard Performance Evaluation Corporation



## Notes/Tuning Information (Continued)

```
  300.twolf:    -fast                +FDO                shlw32M.lib
BIOS Configuration Notes
  Adjacent Cache Line Prefetch Disabled
```